

ASTRA LED 7100LM 857 AR4 IP66 II CL. WIRE 0,7M PLUG/GN SP10KV 53W

DETAILED CARD



TECHNICAL PARAMETERS

Index:	433337
Ingress protection:	IP66
Impact resistance:	IK08
Rated power of the luminaire [W]*:	53
Luminous flux [lm]*:	7100
Colour temperature [K]:	5700
SDCM:	≤ 3
Colour rendering index:	>80
Electrical protection class:	II
Energy efficiency class:	D

CHARACTERISTICS

Streetlight LED fitting with high luminous flux (max 153 lm/W) and an integrated energy-saving LED module. The self-cleaning body made of polypropylene (PP) with fibreglass (GF) and the grip made of aluminium. Thanks to the directional lens (made of PC), the light distribution meets the requirements of PN-EN 13201 lighting class. IP66 ingress protection class and IK08 impact-rating features make this fitting extremely tight and shock-resistant (vandal-resistant). Integrated, step-regulated grip allows to set the fitting by 5 degrees in the range of: -5° to +15° (peak to pole); -15° to +5° (side to boom). Options: any RAL color. RCR sensor controlled by remote control.

APPLICATION

Luminaire applicable to: streets, local roads, bicycle paths, alleys, pavements, car parks and squares. Installation and mounting: lateral side entry, post-top mounting. Mounting grip integrated with the fitting.


ASTRA LED 7100LM 857 AR4 IP66 II CL. WIRE 0,7M PLUG/GN SP10KV 53W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	433337	Mounting dimensions [mm]:	63
EAN:	5905963433337	Impact resistance:	IK08
Light source:	LED module	Ingress protection:	IP66
Rated power of the luminaire [W]:	53	Mounting version:	na słupie: szczytowy lub z wysięgnikiem
Supply voltage [V]:	220-240	Working temperature [°C]:	from -20 to +35
Frequency [Hz]:	50-60	Tilt angle adjustment [°]:	-5 do +15
Luminous flux [lm]:	7100	Lateral surface (SCx) [m2]:	0.170
Luminous efficacy [lm/W]:	134	Wire type:	H07RN-F
Energy efficiency class:	D	Cable length [m]:	0.70
Electrical protection class:	II	Number on the palette [pcs]:	62
Colour temperature [K]:	5700	Net weight [kg]:	1.900
Colour rendering index:	>80	Category type:	street lighting
SDCM:	≤ 3	LED lifespan L80B20 [h]:	75000
Power factor:	0.97	Light distribution type:	symetryczny/uliczny
Diffuser material:	PC	Surge protection [kV]:	10
Diffuser type:	matrix led	Optics:	AR4
Diffuser colour:	transparent	CE certificate:	102/2023
Material of the body:	PP+FG	ENEC Certificate:	0324/ENEC/23
Colour of the body:	gray	Manual:	Download PDF
Dimensions (H/W/T/S) [mm]:	640/233/113		

LIGHT CURVES



ASTRA LED 7100LM 857 AR4 IP66 II CL. WIRE 0,7M PLUG/GN SP10KV 53W

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
314049	wall holder (galvanized)
314056	wall holder (grey)
UL00229	mounting grip 78 mm



wall holder (galvanized) (314049)



wall holder (grey) (314056)



mounting grip 78 mm (UL00229)

Card creation date: 02 February 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 102/2023