

ASTRA LED VD 5650LM 830 AR4 IP66 II CL. WIRE 0,7M PLUG/GN SP10KV 52W

DETAILED CARD



TECHNICAL PARAMETERS

Index:	433276
Ingress protection:	IP66
Impact resistance:	IK08
Rated power of the luminaire [W]*:	52
Luminous flux [lm]*:	5650
Colour temperature [K]:	3000
SDCM:	≤ 5
Colour rendering index:	>80
Electrical protection class:	II
Energy efficiency class:	E

CHARACTERISTICS

Streetlight LED fitting with high luminous flux (max 153 lm/W) and an integrated energy-saving LED module. The self-cleaning body made of polypropylene (PP) with fibreglass (GF) and the grip made of aluminium. Thanks to the directional lens (made of PC), the light distribution meets the requirements of PN-EN 13201 lighting class. IP66 ingress protection class and IK08 impact-rating features make this fitting extremely tight and shock-resistant (vandal-resistant). Integrated, step-regulated grip allows to set the fitting by 5 degrees in the range of: -5° to +15° (peak to pole); -15° to +5° (side to boom). Options: any RAL color. RCR sensor controlled by remote control.

APPLICATION

Luminaire applicable to: streets, local roads, bicycle paths, alleys, pavements, car parks and squares. Installation and mounting: lateral side entry, post-top mounting. Mounting grip integrated with the fitting.


ASTRA LED VD 5650LM 830 AR4 IP66 II CL. WIRE 0,7M PLUG/GN SP10KV 52W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	433276	Dimensions (H/W/T/S) [mm]:	640/233/113
EAN:	5905963433276	Mounting dimensions [mm]:	63
Rated power of the luminaire [W]:	52	Impact resistance:	IK08
Light source:	LED module	Ingress protection:	IP66
Colour temperature [K]:	3000	Mounting version:	na słupie: szczytowy lub z wysięgnikiem
Luminous flux [lm]:	5650	Working temperature [°C]:	from -40 to +35
Optics:	AR4	Tilt angle adjustment [°]:	-5 do +15
Luminous efficacy [lm/W]:	109	Lateral surface (SCx) [m2]:	0.170
Energy efficiency class:	E	Wire type:	H07RN-F
Electrical protection class:	II	Cable length [m]:	0.70
Colour rendering index:	>80	Number on the palette [pcs]:	62
SDCM:	≤ 5	Net weight [kg]:	1.900
Power factor:	0.99	Category type:	street lighting
Diffuser material:	PC	LED lifespan L80B20 [h]:	45000
Diffuser type:	matrix led	Light distribution type:	symetryczny/uliczny
Diffuser colour:	transparent	Surge protection [kV]:	10
Material of the body:	PP+FG	CE certificate:	52/2023
Colour of the body:	gray	ENEC Certificate:	
		Manual:	Download PDF

LIGHT CURVES



ASTRA LED VD 5650LM 830 AR4 IP66 II CL. WIRE 0,7M PLUG/GN SP10KV 52W

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
314049	wall holder (galvanized)
314056	wall holder (grey)
UL00229	mounting grip 78 mm



wall holder (galvanized) (314049)



wall holder (grey) (314056)



mounting grip 78 mm (UL00229)

Card creation date: 02 February 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 52/2023