ASTRA LED 24V 2780LM 830 AR3 IP66 III CL. 20W

DETAILED CARD





TECHNICAL PARAMETERS

Index:	709715
Ingress protection:	IP66
Impact resistance:	IK08
Rated power of the luminaire [W]*:	20
Luminous flux of the luminaire [lm] - range:	2780
Colour temperature [K]:	3000
SDCM:	5
Color rendering index (Ra) >:	80
Electrical protection class:	III
Energy efficiency class:	С

CHARACTERISTICS

Streetlight LED fitting with high luminous flux (max 153 lm/W) and an integrated energy-saving LED module. The self-cleaning body made of polypropylene (PP) with fibreglass (GF) and the grip made of aluminium. Thanks to the directional lens (made of PC), the light distribution meets the requirements of PN–EN 13201 lighting class. IP66 ingress protection class and IK08 impact-rating features make this fitting extremely tight and shock-resistant (vandal-resistant). Integrated, step-regulated grip allows to set the fitting by 5 degrees in the range of: -5° to +15° (peak to pole); -15° to +5° (side to boom). The luminaire is designed to be powered by photovoltaic panels, wind turbines of both off-grid and on-grid mixed systems or other sources with an output voltage of 24V DC. +- 15%

APPLICATION

Streetlight fitting used in open spaces to lighten: streets, local roads, bicycle paths, alleys, pavements, car parks and squares. Installation and Mounting: lateral side entry, post-top mounting. Mounting grip integrated with the fitting.



ASTRA LED 24V 2780LM 830 AR3 IP66 III CL. 20W


DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	709715
EAN:	5905963709715
Light source:	LED module
Rated power of the luminaire [W]:	20
Luminous flux of the luminaire [lm] - range:	2780
Luminous efficacy [lm/W]:	139
Energy efficiency class:	С
Electrical protection class:	III
Colour temperature [K]:	3000
Color rendering index (Ra) >:	80
SDCM:	5
Diffuser material:	PC
Diffuser type:	transparent
Diffuser colour:	transparent
Optics:	AR3
Material of the body:	PP+FG

Dimensions (H/W/T/S) [mm]:	640/233/113
Mounting dimensions [mm]:	Ø60
Impact resistance:	IK08
Ingress protection:	IP66
Working temperature [°C]:	from -20 to +35
Lateral surface (SCx) [m2]:	0.018
Number on the palette [pcs]:	62
Net weight [kg]:	1.900
DC voltage range [V]:	20 - 28
Category type:	street lighting
Supply voltage [V]:	24
Colour of the body:	grey
Mounting version:	side, top
Warranty [years]:	6
CE certificate:	22/2024
Manual:	Download PDF

LIGHT CURVES





ASTRA LED 24V 2780LM 830 AR3 IP66 III CL. 20W

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
598357	Pole adapter 80/60 ALU
UL00214	Adjustable bracket Astra LED/Astra LED BASIC aluminium grey RAL 9006 diameter 64 mm Corona 2 LED







Adjustable bracket Astra LED/Astra LED BASIC aluminium grey RAL 9006 diameter 64 mm Corona 2 LED (UL00214)

Card creation date: 05 February 2024



