

# ASTRA LED 24V 3070LM 857 AR3 IP66 III CL. 20W

DETAILED CARD



## TECHNICAL PARAMETERS

Index:	709623
Ingress protection:	IP66
Impact resistance:	IK08
Rated power of the luminaire [W]*:	20
Luminous flux of the luminaire [lm] - range:	3070
Colour temperature [K]:	5700
SDCM:	≤ 5
Colour rendering index:	>80
Electrical protection class:	III
Energy efficiency class:	C

## CHARACTERISTICS

Streetlight LED fitting with high luminous flux (max 153 lm/W) and an integrated energy-saving LED module. The self-cleaning body made of polypropylene (PP) with fibreglass (GF) and the grip made of aluminium. Thanks to the directional lens (made of PC), the light distribution meets the requirements of PN-EN 13201 lighting class. IP66 ingress protection class and IK08 impact-rating features make this fitting extremely tight and shock-resistant (vandal-resistant). Integrated, step-regulated grip allows to set the fitting by 5 degrees in the range of: -5° to +15° (peak to pole); -15° to +5° (side to boom). The luminaire is designed to be powered by photovoltaic panels, wind turbines of both off-grid and on-grid mixed systems or other sources with an output voltage of 24V DC. +/- 15%

## APPLICATION

Streetlight fitting used in open spaces to lighten: streets, local roads, bicycle paths, alleys, pavements, car parks and squares. Installation and Mounting: lateral side entry, post-top mounting. Mounting grip integrated with the fitting.


# ASTRA LED 24V 3070LM 857 AR3 IP66 III CL. 20W

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Index:	709623	Dimensions (H/W/T/S) [mm]:	640/233/113
Rated power of the luminaire [W]:	20	Mounting dimensions [mm]:	Ø60
EAN:	5905963709623	Impact resistance:	IK08
Colour temperature [K]:	5700	Ingress protection:	IP66
Light source:	LED module	Working temperature [°C]:	from -20 to +35
Luminous flux of the luminaire [lm] - range:	3070	Lateral surface (SCx) [m2]:	0.018
Luminous efficacy [lm/W]:	154	Number on the palette [pcs]:	62
Energy efficiency class:	C	Net weight [kg]:	1.900
Electrical protection class:	III	DC voltage range [V]:	20 - 28
Diffuser type:	transparent	Category type:	street lighting
Optics:	AR3	Supply voltage [V]:	24
Colour rendering index:	>80	Colour of the body:	grey
SDCM:	≤ 5	Mounting version:	side, top
Diffuser material:	PC	Warranty [years]:	6
Diffuser colour:	transparent	CE certificate:	<a href="#">22/2024</a>
Material of the body:	PP+FG	Manual:	<a href="#">Download PDF</a>

## LIGHT CURVES



# ASTRA LED 24V 3070LM 857 AR3 IP66 III CL. 20W

DETAILED CARD

## ACCESSORIES AVAILABLE


index	Name
UL00229	mounting grip 78 mm



mounting grip 78 mm (UL00229)

Card creation date: 05 February 2024  
The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 22/2024