TERRA 3 LED Z 1195X230MM X2 3000LM 840 WHITE GLOSS (20W)

DETAILED CARD





TECHNICAL PARAMETERS

Index: 441417

Rated power of the luminaire [W]*: 20

Luminous flux [lm]*: 3000

Colour temperature [K]: 4000

Colour rendering index: 80

Material of the body: powder coated steel

Colour of the body: white gloss

Dimensions (H/W/T/S) [mm]: 1195/230/38

Mounting version: suspended

Energy efficiency class: C

CHARACTERISTICS

A luminaire equipped with energy-efficient LED modules characterised by high luminous flux. The low side profile provides an aesthetically pleasing, timeless appearance. Robust, compact construction. Made of powder-coated steel sheet. Patented high-performance HE reflector guarantees high efficiency while effectively eliminating glare.

APPLICATION

The versatile luminaire is designed for indoor use in offices or general utility rooms. Its high luminous parameters make it suitable as the main source of light and conducive to work requiring visual focus. The luminaire is suitable for both new applications and the replacement of traditional fluorescent lamps with energy-efficient LED solutions.



TERRA 3 LED Z 1195X230MM X2 3000LM 840 WHITE GLOSS (20W)


DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	441417
EAN:	5905963441417
Light source:	LED
Rated power of the luminaire [W]:	20
Luminous flux [Im]:	3000
Luminous efficacy [lm/W]:	150
Ingress protection:	IP20
Energy efficiency class:	С
Electrical protection class:	Ш
Colour temperature [K]:	4000
Colour rendering index:	80
Beam angle [°]:	60
Diffuser material:	PC
Diffuser type:	matrix led
Diffuser colour:	transparent
Optics material:	PC
Optics:	lens
Material of the body:	powder coated steel

hite gloss	
1195/230/38	
ıspended	
5	
400	
offers	
1	
00/60	
ymmetric	
om -20 to +35	
50000	
00000	
0000	
2/2025	
ownload PDF	

LIGHT CURVES






TERRA 3 LED Z 1195X230MM X2 3000LM 840 WHITE GLOSS (20W)


DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
999543	Plasterboard recessing kit 630x630 white (steel version)
374845	Frame adapter KG 635x635 WHITE
998966	Frame steel white structure RAL9016 600x600 SM "well effect"







Frame steel white structure RAL9016 600x600 SM "well effect" (998966)

