

# TERRA 3 LED Z 595X595MM X2 3300LM 830 DALI WHITE GLOSS (28W)

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Index:</b>	441165
<b>Rated power of the luminaire [W]*:</b>	28
<b>Luminous flux [lm]*:</b>	3300
<b>Colour temperature [K]:</b>	3000
<b>Colour rendering index:</b>	>80
<b>Material of the body:</b>	powder coated steel
<b>Colour of the body:</b>	white gloss
<b>Dimensions (H/W/T/S) [mm]:</b>	595/595/38
<b>Mounting version:</b>	suspended
<b>Energy efficiency class:</b>	D

## CHARACTERISTICS

A luminaire equipped with energy-efficient LED modules characterised by high luminous flux. The low side profile provides an aesthetically pleasing, timeless appearance. Robust, compact construction. Made of powder-coated steel sheet. Patented high-performance HE reflector guarantees high efficiency while effectively eliminating glare.

Available mounting versions: surface mounted, flush mounted in modular ceilings or pendant. The surface-mounted version features solutions for fast and safe installation.

UGR < 19

The Unified Glare Rating is an indicator that characterises glare. The lower the Unified Glare Rating (UGR), the lower the glare. In the case of lamps for office spaces, UGR<19 values translate into, among other things, greater working comfort, reduction of errors and fatigue. The UGR value also depends on a number of factors that characterise the room and the location of the observer. Dedicated computer programmes, among others, are used to precisely determine the degree of glare for specific conditions.

## APPLICATION

The versatile luminaire is designed for indoor use in offices or general utility rooms. Its high luminous parameters make it suitable as the main source of light and conducive to work requiring visual focus. The luminaire is suitable for both new applications and the replacement of traditional fluorescent lamps with energy-efficient LED solutions.

# TERRA 3 LED Z 595X595MM X2 3300LM 830 DALI WHITE GLOSS (28W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Rated power of the luminaire [W]:	28	Beam angle [°]:	60
Index:	441165	Diffuser material:	PC
Colour temperature [K]:	3000	Diffuser type:	matrix led
EAN:	5905963441165	Diffuser colour:	transparent
Luminous flux [lm]:	3300	Optics material:	PC
Light source:	LED	Optics:	lens
DIMM DALI:	1	Material of the body:	powder coated steel
Colour of the body:	white gloss	Number on the palette [pcs]:	40
Luminous efficacy [lm/W]:	118	Net weight [kg]:	4.200
Version:	2x1	Category type:	louvres
Ingress protection:	IP20	Mounting dimensions [mm]:	160
Energy efficiency class:	D	Light distribution type:	symmetric
Dimensions (H/W/T/S) [mm]:	595/595/38	Warranty [years]:	5
Electrical protection class:	II	CE certificate:	<a href="#">23/2024</a>
Mounting version:	suspended	Manual:	<a href="#">Download PDF</a>
Colour rendering index:	>80	Working temperature [°C]:	from -20 to +35

## LIGHT CURVES



# TERRA 3 LED Z 595X595MM X2 3300LM 830 DALI WHITE GLOSS (28W)

DETAILED CARD

## ACCESSORIES AVAILABLE

index	Name
999543	Plasterboard recessing kit 630x630 white (steel version)
374845	Frame adapter KG 635x635 WHITE
998966	Frame steel white structure RAL9016 600x600 SM "well effect"



Plasterboard recessing kit 630x630 white (steel version) (999543)



Frame steel white structure RAL9016 600x600 SM "well effect" (998966)

Card creation date: 19 June 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 23/2024