

# ALTEZZO L 100 1200MM 700LM 840 AS IP65 PIR RAL7016 6W (120) IOT

DETAILED CARD



## TECHNICAL PARAMETERS

Rated power of the luminaire [W]*:	6
Luminous flux [lm]*:	700
Luminous efficacy [lm/W]:	117
Energy efficiency class:	D
Electrical protection class:	I
Colour temperature [K]:	3000
Colour rendering index:	>80
Beam angle [°]:	110
Diffuser material:	PC
Optics:	lens

## CHARACTERISTICS

Altezzo L 100 is a family of outdoor lamps with a modern design. They are offered in four sizes - with heights ranging from 600 mm to 1500 mm. Their impact-resistant (IK08) and compact profile (100 mm x 40 mm) is made of aluminum in graphite color (RAL 7016). The light module consists of leds with a life span of up to 196,000 h, with lenses made of PMMA and a durable polycarbonate diffuser.

## APPLICATION

The wide range of luminous fluxes in the Altezzo L 100 lamp series allows to design energy-efficient lighting in the amount required by the norm, both in walking alleys and building surroundings. Versions with lower wattages will work well in parks and gardens for illuminating small architecture.

The lamps are designed for operation in low and high temperatures from -30°C to +50 °C and in harsh weather conditions. They are characterized by a very high IP65 tightness.

## DETAILS

The selection of the foundation for the lighting column, in accordance with the Building Act, rests with the designer, with the relevant qualifications. The designer is also obliged to check the standard solution from the lighting manufacturer's offer, as he knows, among other things, the soil and water conditions in the designed area. If the dedicated foundation does not provide the safe conditions specified in the design, a suitable one should be selected from outside the lighting manufacturer's offer, with an anchor spacing of 180x180 - 220x220mm. As standard, in the case of **Altezzo L100**, universal 13kg foundations are used for garden lamps or FBO 35/7.5 M6 foundations for taller posts and/or more difficult ground and water conditions.

# ALTEZZO L 100 1200MM 700LM 840 AS IP65 PIR RAL7016 6W (120) IOT

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Index:	986864	Dimensions (H/W/T/S) [mm]:	235/140/1200
EAN:	5905963986864	Mounting dimensions [mm]:	75x75 - 90x90
Light source:	LED module	Impact resistance:	IK08
Rated power of the luminaire [W]:	6	Ingress protection:	IP65
Luminous flux [lm]:	700	Mounting version:	on a foundation
Luminous efficacy [lm/W]:	117	Working temperature [°C]:	od - 25 do + 50
Energy efficiency class:	D	Dimensions of single box [mm]:	1550/210/200
Electrical protection class:	I	Number on the palette [pcs]:	18
Colour temperature [K]:	3000	Net weight [kg]:	4
Colour rendering index:	>80	Corridor function:	yes
Beam angle [°]:	110	PIR:	yes
Light distribution type:	asymmetric	DIMM DALI:	yes
Diffuser material:	PC	Control:	yes
Optics:	lens	Category type:	Park and city lighting
Optics material:	PMMA	Warranty [years]:	5
Material of the body:	aluminium	CE certificate:	<a href="#">93/2023</a>
Colour of the body:	RAL7016	Manual:	<a href="#">Download PDF</a>

Card creation date:15 March 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 93/2023