

INDUSTRY SLIM LED 1177MM 9500LM 840 IP66 SW (57W)

DETAILED CARD



INDUSTRY SLIM LED 1177MM 9500LM 840 IP66 SW (57W)

DETAILED CARD

TECHNICAL PARAMETERS

| | |
|---|-------------|
| Index: | 838071 |
| Ingress protection: | IP66 |
| Impact resistance: | IK09 |
| Rated power of the luminaire [W]*: | 57 |
| Luminous flux [lm]*: | 9500 |
| Colour temperature [K]: | 4000 |
| Material of the body: | aluminium |
| Colour of the body: | silver |
| Diffuser material: | PC |
| Diffuser type: | transparent |

CHARACTERISTICS

Industry Slim Led - a brand new industrial luminaire is characterized by high luminous flux and very high luminous efficiency >160 lm/W, which makes this luminaire highly energy-efficient and environmentally friendly. It is distinguished by its very high IP66 tightness. It owes this tightness to its well-thought-out design. The polycarbonate diffuser is permanently attached to the housing with a durable silicone gasket. This means that in addition to the tightness thus achieved, the light module is protected from uncontrolled interference and access to the LEDs. The tightness of the lamp, is ensured by the gland, which screwed tightens the gasket and prevents the penetration of dust or moisture and water. Industry Slim Led allows for pendant or surface mounting.

APPLICATION

The luminaire is designed to illuminate industrial and warehouse facilities, due to its minimal dimensions, also in hard-to-reach places. The Industry Slim Led luminaire is available in various versions: with different optics, wide, narrow, and dedicated to high-bay light distribution, and five types of the diffuser, including an anti-glare diffuser.

DETAILS




INDUSTRY SLIM LED 1177MM 9500LM 840 IP66 SW (57W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

| | | | |
|-----------------------------------|---------------|--|---|
| Index: | 838071 | Diffuser colour: | transparent |
| EAN: | 5905963838071 | Material of the body: | aluminium |
| Light source: | LED module | Colour of the body: | silver |
| Rated power of the luminaire [W]: | 57 | Dimensions (H/W/T/S) [mm]: | 1177/50/75 |
| Luminous flux [lm]: | 9500 | Mounting dimensions [mm]: | 800 |
| Supply voltage [V]: | 220 - 240 | Impact resistance: | IK09 |
| Frequency [Hz]: | 50-60 | Ingress protection: | IP66 |
| Luminous efficacy [lm/W]: | 167 | Mounting version: | surface, suspended |
| Energy efficiency class: | B | Working temperature [°C]: | from -25 to +35 |
| Electrical protection class: | I | Number on the palette [pcs]: | 168 |
| Colour temperature [K]: | 4000 | Net weight [kg]: | 2.100 |
| Color rendering index (Ra) >: | 80 | Light distribution type: | SW |
| SDCM: | 3 | Warranty [years]: | 5 |
| LED lifespan L70B50 [h]: | 150000 | CE certificate: | 31/2024 |
| LED lifespan L80B10 [h]: | 100000 | ENEC Certificate: | 0362/ENEC/24 |
| LED lifespan L90B10 [h]: | 45000 | Manual: | Download PDF |
| Beam angle [°]: | 80 | Environmental Product Declaration (EPD): | 852/2025 |
| Surge protection [kV]: | 1 | ISO Certificates: | 9001:2015, 14001:2015, 45001:2018, 50001:2018 |
| Diffuser material: | PC | Plik LDT: | Download |
| Diffuser type: | transparent | | |

LIGHT CURVES



INDUSTRY SLIM LED 1177MM 9500LM 840 IP66 SW (57W)

DETAILED CARD

ACCESSORIES AVAILABLE

| index | Name |
|----------|---|
| 908200 | TYTAN LED. ATLAS LED. INDUSTRY LED - adjustable handle (set of 2) |
| 60000006 | M16 stuffing box plug various PA black M-16 - BPM-21 |



TYTAN LED. ATLAS LED. INDUSTRY LED - adjustable handle (set of 2) (908200)



M16 stuffing box plug various PA black M-16 - BPM-21 (60000006)

Card creation date: 25 March 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 31/2024