

OCULUS LED 21950LM 840 IP66 I CL. 75D SP10KV 126W (F)

DETAILED CARD



TECHNICAL PARAMETERS

Nominal power [W]:	126
Luminous flux [lm]*:	21950
Supply voltage [V]:	122-277
Frequency [Hz]:	50-60
Luminous efficacy [lm/W]:	166
Energy efficiency class:	B
Electrical protection class:	I
Colour temperature [K]:	4000
Dimensions (H/W/T/S) [mm]:	122/371
Impact resistance:	IK09

CHARACTERISTICS

OCULUS LED F is a HIGH-BAY luminaire from the NEXT GEN product line, constituting a new generation of luminaires dedicated to LED technology. The designed-from-scratch body – made of die-cast aluminium and powder coated – uses natural conduction and convection processes, which have a positive effect on luminaire's heat management. The shape of the body with an integrated, effective heat sink and high-quality materials ensure maximum heat dissipation from the LED module. The driver's external compartment, separated from the body, guarantees optimal thermal working conditions for the power supply system. This enables the luminaire to work in an ambient temperature of max 60°C. LEDs from a reputable manufacturer and new LED modules enable very high luminous efficiency: max 176 lm/W. This guarantees that the required lighting level and significant energy savings are achieved. The diffuser and optical system are composed of precise linear lenses made of polycarbonate (PC). There are 3 dedicated ranges of light distribution available: 55°, 75°, 105°. GLASS version with tempered glass (without lenses) and 105° distribution is also available.

Standard equipped with a 0.3 m long H07RN-F cable terminated with an additional male and female connector, which makes the assembly easier and more convenient.

Available version with radio motion sensor:

- allowing additional savings in electricity consumption
- convenient change of parameters by remote control (to be purchased separately).

Its design is adapted for suspended mounting and surface mounting (ceiling and wall) requiring the use of additional accessories.

APPLICATION

The luminaire is intended for suspended mounting (using chains, wires, etc.) both indoors and outdoors. It will prove perfect for manufacturing plants and halls as well as large-format warehouses and logistics centres.

OCULUS LED 21950LM 840 IP66 I CL. 75D SP10KV 126W (F)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	964046/F	Diffuser type:	transparent
Nominal power [W]:	126	Optics:	lens
Rated power of the luminaire [W]:	132.20	Optics material:	PC
Luminous flux [lm]:	21950	Material of the body:	powder coated aluminium
Supply voltage [V]:	122-277	Colour of the body:	grey
Frequency [Hz]:	50-60	Dimensions (H/W/T/S) [mm]:	122/371
Luminous efficacy [lm/W]:	166	Impact resistance:	IK09
Energy efficiency class:	B	Ingress protection:	IP65
Electrical protection class:	I	Working temperature [°C]:	from -40 to +50
Colour temperature [K]:	4000	Cable length [m]:	0.30
Colour rendering index:	>80	Dimensions of single box [mm]:	135/372/372
SDCM:	≤ 3	Number on the palette [pcs]:	66
Power factor:	0.97	Net weight [kg]:	3.420
LED lifespan L70B50 [h]:	196000	Mark D:	yes
LED lifespan L80B20 [h]:	123000	The number of implement units:	1
LED lifespan L90B10 [h]:	60000	Warranty [years]:	5
Beam angle [°]:	75	CE certificate:	33/2024
Surge protection [kV]:	6	HACCP:	852/2004
Diffuser material:	PC	Manual:	Download PDF

OCULUS LED 21950LM 840 IP66 I CL. 75D SP10KV 126W (F)

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
964244	OCULUS LED - RCR motion sensor
964886	OCULUS LED - universal handle-lack of compatibility with Dali version 294W
964893	OCULUS LED - surface mounting handle-lack of compatibility with Dali version 294W
964862	OCULUS LED - protective grid
963674	OCULUS LED - RCR / PIR DALI motion sensor
WSEL438	Remote control for motion sensor HD01R
WSEL415	WSEL415 Remote control for - PIR sensor



OCULUS LED - RCR motion sensor (964244)



OCULUS LED - universal handle-lack of compatibility with Dali version 294W (964886)



OCULUS LED - surface mounting handle-lack of compatibility with Dali version 294W (964893)



OCULUS LED - protective grid (964862)



OCULUS LED - RCR / PIR DALI motion sensor (963674)



Remote control for motion sensor HD01R (WSEL438)



WSEL415 Remote control for - PIR sensor (WSEL415)