

OCULUS LED 22700LM 840 IP66 I CL. 105D SP10KV 126W (F)

DETAILED CARD



TECHNICAL PARAMETERS

Nominal power [W]:	126
Luminous flux [lm]*:	22700
Supply voltage [V]:	122-277
Frequency [Hz]:	50-60
Luminous efficacy [lm/W]:	172
Energy efficiency class:	B
Electrical protection class:	I
Colour temperature [K]:	4000
Dimensions (H/W/T/S) [mm]:	122/371
Impact resistance:	IK09

CHARACTERISTICS

OCULUS LED F is a HIGH-BAY luminaire from the NEXT GEN product line, constituting a new generation of luminaires dedicated to LED technology. The designed-from-scratch body – made of die-cast aluminium and powder coated – uses natural conduction and convection processes, which have a positive effect on luminaire's heat management. The shape of the body with an integrated, effective heat sink and high-quality materials ensure maximum heat dissipation from the LED module. The driver's external compartment, separated from the body, guarantees optimal thermal working conditions for the power supply system. This enables the luminaire to work in an ambient temperature of max 60°C. LEDs from a reputable manufacturer and new LED modules enable very high luminous efficiency: max 176 lm/W. This guarantees that the required lighting level and significant energy savings are achieved. The diffuser and optical system are composed of precise linear lenses made of polycarbonate (PC). There are 3 dedicated ranges of light distribution available: 55°, 75°, 105°. GLASS version with tempered glass (without lenses) and 105° distribution is also available.

Standard equipped with a 0.3 m long H07RN-F cable terminated with an additional male and female connector, which makes the assembly easier and more convenient.

Available version with radio motion sensor:

- allowing additional savings in electricity consumption
- convenient change of parameters by remote control (to be purchased separately).

Its design is adapted for suspended mounting and surface mounting (ceiling and wall) requiring the use of additional accessories.

APPLICATION

The luminaire is intended for suspended mounting (using chains, wires, etc.) both indoors and outdoors. It will prove perfect for manufacturing plants and halls as well as large-format warehouses and logistics centres.

OCULUS LED 22700LM 840 IP66 I CL. 105D SP10KV 126W (F)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	964039/F	Diffuser material:	PC
Nominal power [W]:	126	Diffuser type:	transparent
Rated power of the luminaire [W]:	132.20	Material of the body:	powder coated aluminium
Luminous flux [lm]:	22700	Colour of the body:	grey
Supply voltage [V]:	122-277	Dimensions (H/W/T/S) [mm]:	122/371
Frequency [Hz]:	50-60	Impact resistance:	IK09
Luminous efficacy [lm/W]:	172	Ingress protection:	IP65
Energy efficiency class:	B	Working temperature [°C]:	from -40 to +50
Electrical protection class:	I	Cable length [m]:	0.30
Colour temperature [K]:	4000	Dimensions of single box [mm]:	135/372/372
Colour rendering index:	>80	Number on the palette [pcs]:	66
SDCM:	≤ 3	Net weight [kg]:	3.420
Power factor:	0.97	Mark D:	yes
LED lifespan L70B50 [h]:	196000	The number of implement units:	1
LED lifespan L80B20 [h]:	123000	Warranty [years]:	5
LED lifespan L90B10 [h]:	60000	CE certificate:	33/2024
Beam angle [°]:	105	HACCP:	852/2004
Surge protection [kV]:	6	Manual:	Download PDF

OCULUS LED 22700LM 840 IP66 I CL. 105D SP10KV 126W (F)

DETAILED CARD

ACCESSORIES AVAILABLE


index	Name
964244	OCULUS LED - RCR motion sensor
964886	OCULUS LED - universal handle-lack of compatibility with Dali version 294W
964893	OCULUS LED - surface mounting handle-lack of compatibility with Dali version 294W
964862	OCULUS LED - protective grid
963674	OCULUS LED - RCR / PIR DALI motion sensor
WSEL438	Remote control for motion sensor HD01R
WSEL415	WSEL415 Remote control for - PIR sensor



OCULUS LED - RCR motion sensor (964244)



OCULUS LED - universal handle-lack of compatibility with Dali version 294W (964886)



OCULUS LED - surface mounting handle-lack of compatibility with Dali version 294W (964893)



OCULUS LED - protective grid (964862)



OCULUS LED - RCR / PIR DALI motion sensor (963674)



Remote control for motion sensor HD01R (WSEL438)



WSEL415 Remote control for - PIR sensor (WSEL415)

Card creation date: 03 April 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 33/2024