

# TIARA 2 LED S 4900LM 740 RM7HE IP66 II CL. DALI (29W)

DETAILED CARD



## TECHNICAL PARAMETERS

|   |        |
|---|--------|
| <b>Index:</b>                             | 434136 |
| <b>Ingress protection:</b>                | IP66   |
| <b>Impact resistance:</b>                 | IK10   |
| <b>Rated power of the luminaire [W]*:</b> | 29     |
| <b>Luminous flux [lm]*:</b>               | 4900   |
| <b>Colour temperature [K]:</b>            | 4000   |
| <b>Colour rendering index:</b>            | > 70   |
| <b>Electrical protection class:</b>       | II     |
| <b>Optics:</b>                            | RM7HE  |

## CHARACTERISTICS

TIARA 2 LED a new generation of LED road luminaires. It uses directional multi-lens arrays made of PMMA, with each lens having the same optics, ensuring that the light characteristics remain constant over time. The luminaire's dual-chamber design maintains the integrity of the optical chamber during installation work and the opening of the electrical chamber. As standard, the luminaire offers tool-free access to the electrical fixtures using two independent clips, which, if desired and needed to protect against vandalism or uncontrolled opening, can optionally be permanently secured with screws or a seal. The upper part of the luminaire, has dedicated hinges and a safety cable to prevent falling. Using standard tools, quick and convenient service is possible, allowing replacement of any component without the need to disassemble the entire fixture and make soldered connections. The body and handle made of die-cast aluminum, powder-coated in gray, is characterized by a very high degree of IP66 and IK10 impact resistance. Standard features: ergonomic light module suspension system; NTC luminaire accidental overheating protection; fully programmable DALI driver; available functions for maintaining constant lumen output during CLO and autonomous 5-stage power reduction; filter to prevent condensation; connection terminals; tool-free access. Additional options: NEMA, ZHAGA connectors; interfacing with control systems, RCR motion sensor; anti-vandal protection with screws/seal; additional SP10kV protection outside the power supply, on/off power supply without power reduction function; knife disconnect switch that disconnects voltage if the electrical compartment is opened; design with cable terminated with quick disconnect; painting in any RAL color. Certifications: CE, RoHS, ENEC, ENEC+, Zhaga D4i.

## APPLICATION

Thanks to the use of dedicated optics, it is possible to illuminate objects such as: highways, expressways, national, provincial, county, municipal, city, neighborhood, area lighting. Optics are also available to illuminate: pedestrian crossings, sidewalks and bicycle paths.


# TIARA 2 LED S 4900LM 740 RM7HE IP66 II CL. DALI (29W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

|                                   |                 |  |   |
|-----------------------------------|-----------------|--|---|
| Index:                            | 434136          | Exchangeable source:                     | yes   |
| Rated power of the luminaire [W]: | 29              | Material of the body:                    | powder coated aluminium                     |
| EAN:                              | 5905963434136   | Colour of the body:                      | grey  |
| Luminous flux [lm]:               | 4900            | Dimensions (H/W/T/S) [mm]:               | 424/251/105                                 |
| ETIM class:                       | EC000062        | Mounting dimensions [mm]:                | ø60   |
| Luminous efficacy [lm/W]:         | 169             | Impact resistance:                       | IK10  |
| Category type:                    | street lighting | Ingress protection:                      | IP66  |
| Energy efficiency class:          | B               | Mounting version:                        | Top, on pole / Side, on boom                |
| Product line:                     | HE              | Tilt angle adjustment [°]:               | -30° to +120° (peak); -120° to +30° (side)  |
| Colour temperature [K]:           | 4000            | Lateral surface (SCx) [m2]:              | 0.021                                       |
| Version:                          | S               | Working temperature [°C]:                | from -40 to +50                             |
| Colour rendering index:           | > 70            | Control:                                 | Yes + 5-stage power reduction               |
| Light source:                     | LED module      | Protection type:                         | NTC + ESD                                   |
| Electrical protection class:      | II              | Vandalproof:                             | yes   |
| Optics:                           | RM7HE           | Net weight [kg]:                         | 4.290                                       |
| Supply voltage [V]:               | 220 - 240       | ULOR:                                    | 0%  |
| DIMM DALI:                        | yes             | Photobiological safety:                  | RG0 - exempt (no photobiological hazard)    |
| Frequency [Hz]:                   | 50 - 60         | Technical Warranty:                      | 5 with the possibility of extension to 10   |
| SDCM:                             | ≤ 4             | ENEC Certificate:                        | <a href="#">0410/ENEC/25; 0141/ENEC+/25</a> |
| Power factor:                     | 0.96            | CE certificate:                          | <a href="#">91/2023</a>                     |
| Surge protection [kV]:            | 10              | Zhaga-D4i:                               | <a href="#">ZG407220042023</a>              |
| Diffuser material:                | toughened glass | Environmental Product Declaration (EPD): | <a href="#">682/2024</a>                    |
| Diffuser type:                    | transparent     | Manual:                                  | <a href="#">Download PDF</a>                |
| Optics material:                  | PMMA + PC       | LED lifespan L95B10 [h]:                 | 100000                                      |

## LIGHT CURVES



# TIARA 2 LED S 4900LM 740 RM7HE IP66 II CL. DALI (29W)

DETAILED CARD

## ACCESSORIES AVAILABLE

| index   | Name   |
|---------|--|
| 314049  | wall holder (galvanized)                           |
| 314056  | wall holder (grey)                                 |
| UL01350 | Handle fi 76mm for Tiara 2 LED M and Tiara 2 LED S |



wall holder (galvanized) (314049)



wall holder (grey) (314056)

Card creation date: 26 March 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 91/2023