

ASTRA S LED PRO 1970LM 840 AR5 IP66 I CL. WIRE 0,7M PLUG/GN 12W

DETAILED CARD



TECHNICAL PARAMETERS

| | |
|------------------------------------|--------|
| Index: | 436086 |
| Ingress protection: | IP66 |
| Rated power of the luminaire [W]*: | 12 |
| Luminous flux [lm]*: | 1970 |
| Colour temperature [K]: | 4000 |
| Colour rendering index: | 80 |
| Electrical protection class: | I |
| Optics: | AR5 |
| Colour of the body: | grey |
| Luminous efficacy [lm/W]: | 164 |

CHARACTERISTICS

LED road luminaire with high luminous efficiency and energy-saving integrated LED module. Self-cleaning body made of polypropylene (PP) with fibreglass (FG), handle made of aluminium. The luminaire uses directional lens matrices (made of polycarbonate PC). The luminaire is characterised by a high IP66 ingress protection rating and mechanical impact resistance. The integrated bracket, which is adjustable in increments of 5 degrees, allows adjustment from: -5° to +15° (top, on pole); -5° to +15° (side, on boom). Supplied with 0.7m of H07RN-F cable as standard.

APPLICATION

Road luminaire suitable for illumination of: streets and municipal, local, internal and neighbourhood roads, cycle paths, alleys, pavements, car parks, squares, private properties and all open spaces.

ASTRA S LED PRO 1970LM 840 AR5 IP66 I CL. WIRE 0,7M PLUG/GN 12W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

| | | | |
|-----------------------------------|-----------------|----------------------------|------------------------------|
| Index: | 436086 | Diffuser type: | matrix led |
| EAN: | 5905963436086 | Optics: | AR5 |
| Category type: | street lighting | Material of the body: | PP+FG |
| Light source: | LED module | Colour of the body: | grey |
| Rated power of the luminaire [W]: | 12 | Dimensions (H/W/T/S) [mm]: | 75/175/500 |
| Supply voltage [V]: | 220 - 240 | Mounting dimensions [mm]: | ø60 |
| Frequency [Hz]: | 50 - 60 | Ingress protection: | IP66 |
| Luminous flux [lm]: | 1970 | Net weight [kg]: | 1.400 |
| Luminous efficacy [lm/W]: | 164 | Warranty [years]: | 5 |
| Energy efficiency class: | B | CE certificate: | 42/2024 |
| Electrical protection class: | I | Manual: | Download PDF |
| Colour temperature [K]: | 4000 | Product line: | PRO |
| Colour rendering index: | 80 | Impact resistance: | IK08 |
| Surge protection [kV]: | 1 | Working temperature [°C]: | from -25 to +45 |
| Diffuser material: | PC | ENEC Certificate: | 0373/ENEC/24 |

LIGHT CURVES

