# ASTRA S LED PRO 3600LM 830 AR5 IP66 II CL. WIRE 0,7M PLUG/GN 25W

DETAILED CARD




## TECHNICAL PARAMETERS

| | |
|---|---|
| **Index:** | 436307 |
| **Ingress protection:** | IP66 |
| **Rated power of the luminaire [W]*:** | 25 |
| **Luminous flux [lm]*:** | 3600 |
| **Colour temperature [K]:** | 3000 |
| **Color rendering index (Ra) >:** | 80 |
| **Electrical protection class:** | II |
| **Optics:** | AR5 |
| **Colour of the body:** | grey |
| **Luminous efficacy [lm/W]:** | 144 |

## CHARACTERISTICS

LED road luminaire with high luminous efficiency and energy-saving integrated LED module. Self-cleaning body made of polypropylene (PP) with fibreglass (FG), handle made of aluminium. The luminaire uses directional lens matrices (made of polycarbonate PC). The luminaire is characterised by a high IP66 ingress protection rating and mechanical impact resistance. The integrated bracket, which is adjustable in increments of 5 degrees, allows adjustment from: -5° to +15° (top, on pole); -5° to +15° (side, on boom). Supplied with 0.7m of H07RN-F cable as standard.

## APPLICATION

Road luminaire suitable for illumination of: streets and municipal, local, internal and neighbourhood roads, cycle paths, alleys, pavements, car parks, squares, private properties and all open spaces.

# ASTRA S LED PRO 3600LM 830 AR5 IP66 II CL. WIRE 0,7M PLUG/GN 25W


DETAILED CARD

## TECHNICAL PARAMETERS TABLE

| | |
|---|---|
| **Index:** | 436307 |
| **EAN:** | 5905963436307 |
| **Category type:** | street lighting |
| **Light source:** | LED module |
| **Rated power of the luminaire [W]:** | 25 |
| **Supply voltage [V]:** | 220 - 240 |
| **Frequency [Hz]:** | 50 - 60 |
| **Luminous flux [lm]:** | 3600 |
| **Luminous efficacy [lm/W]:** | 144 |
| **Energy efficiency class:** | C |
| **Electrical protection class:** | II |
| **Colour temperature [K]:** | 3000 |
| **Color rendering index (Ra) >:** | 80 |
| **Surge protection [kV]:** | 1 |
| **Diffuser material:** | PC |
| **Diffuser type:** | matrix led |
| **Optics:** | AR5 |

| | |
|---|---|
| **Material of the body:** | PP+FG |
| **Colour of the body:** | grey |
| **Dimensions (H/W/T/S) [mm]:** | 75/175/500 |
| **Mounting dimensions [mm]:** | ø60 |
| **Ingress protection:** | IP66 |
| **Net weight [kg]:** | 1.400 |
| **LED lifespan L80B10 [h]:** | 90000 |
| **Cable length [m]:** | 0.70 |
| **Product line:** | PRO |
| **Impact resistance:** | IK08 |
| **Working temperature [°C]:** | from -25 to +45 |
| **Warranty [years]:** | 5 |
| **CE certificate:** | 42/2024 |
| **ENEC Certificate:** | 0373/ENEC/24 |
| **Manual:** | Download PDF |
| **Category of application:** | Street lighting |
| **Plik LDT:** | Download |

## LIGHT CURVES



# ASTRA S LED PRO 3600LM 830 AR5 IP66 II CL. WIRE 0,7M PLUG/GN 25W

DETAILED CARD

## ACCESSORIES AVAILABLE

| index | Name |
|---|---|
| 598357 | Pole adapter 80/60 ALU |
| UL00214 | Adjustable bracket Astra LED/Astra LED BASIC aluminium grey RAL 9006 diameter 64 mm Corona 2 LED |



Pole adapter 80/60 ALU (598357)



Adjustable bracket Astra LED/Astra LED BASIC aluminium grey RAL 9006 diameter 64 mm Corona 2 LED (UL00214)



The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 42/2024

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl