

ASTRA S LED PRO 3870LM 840 AR5 IP66 I CL. DALI WIRE 0,7M PLUG/GN 25W

DETAILED CARD



TECHNICAL PARAMETERS

Index:	436611
Ingress protection:	IP66
Rated power of the luminaire [W]*:	25
Luminous flux [lm]*:	3870
Colour temperature [K]:	4000
Colour rendering index:	80
Electrical protection class:	I
Optics:	AR5
Colour of the body:	grey
Luminous efficacy [lm/W]:	155

CHARACTERISTICS

LED road luminaire with high luminous efficiency and energy-saving integrated LED module. Self-cleaning body made of polypropylene (PP) with fibreglass (FG), handle made of aluminium. The luminaire uses directional lens matrices (made of polycarbonate PC). The luminaire is characterised by a high IP66 ingress protection rating and mechanical impact resistance. The integrated bracket, which is adjustable in increments of 5 degrees, allows adjustment from: -5° to +15° (top, on pole); -5° to +15° (side, on boom). Supplied with 0.7m of H07RN-F cable as standard.

APPLICATION

Road luminaire suitable for illumination of: streets and municipal, local, internal and neighbourhood roads, cycle paths, alleys, pavements, car parks, squares, private properties and all open spaces.

ASTRA S LED PRO 3870LM 840 AR5 IP66 I CL. DALI WIRE 0,7M PLUG/GN 25W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	436611	Optics:	AR5
EAN:	5905963436611	Material of the body:	PP+FG
Category type:	street lighting	Colour of the body:	grey
Light source:	LED module	Dimensions (H/W/T/S) [mm]:	75/175/500
Rated power of the luminaire [W]:	25	Mounting dimensions [mm]:	ø60
Supply voltage [V]:	220 - 240	Ingress protection:	IP66
Frequency [Hz]:	50 - 60	Net weight [kg]:	1.400
Luminous flux [lm]:	3870	Warranty [years]:	5
Luminous efficacy [lm/W]:	155	CE certificate:	42/2024
Energy efficiency class:	C	Manual:	Download PDF
Electrical protection class:	I	Product line:	PRO
Colour temperature [K]:	4000	Impact resistance:	IK08
Colour rendering index:	80	Working temperature [°C]:	from -25 to +45
Surge protection [kV]:	1	DIMM DALI:	yes
Diffuser material:	PC	ENEC Certificate:	0373/ENEC/24
Diffuser type:	matrix led	Plik LDT:	Download

LIGHT CURVES

