

CALLISTO LED EVO 1750LM 15W 830 IP40 I CLASS OPAL WHITE 365MM

DETAILED CARD



TECHNICAL PARAMETERS

Index:	065880
Ingress protection:	IP40
Impact resistance:	IK03
Nominal power [W]:	15
Luminous flux [lm]*:	1750
Colour temperature [K]:	3000
Energy efficiency class:	E
Material of the body:	Galvanized steel
Diffuser material:	glass
Diffuser type:	OPAL

CHARACTERISTICS

Surface mounted, round LED luminaire with a very high luminous flux; includes an integrated energy-saving light source LED GO!. Galvanized steel base, powder coated white; glass diffuser hand-made of multilayer triplex glass which ensures even light distribution. Decorative fitting with an easy-to-clean, simple system mounting the diffuser to the base. Available in four diameters and two finishes: opal and opal mat.

APPLICATION

Surface mounted fitting intended for indoor use in representative rooms and passageways (large conference halls, hotel corridors, studies). Designed for mounting on ceilings and walls. Wide range of diameters and two diffuser versions allow for the same fitting to be used in rooms with different parameters. Well suited to be used as a basic or general interior light source.

CALLISTO LED EVO 1750LM 15W 830 IP40 I CLASS OPAL WHITE 365MM

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Nominal power [W]:	15	Impact resistance:	IK03
Light source:	LED module	Ingress protection:	IP40
Colour temperature [K]:	3000	Mounting version:	surface
Luminous flux [lm]:	1750	Working temperature [°C]:	from -20 to +25
Rated power of the luminaire [W]:	16	Accessories included:	Mounting cross
Luminous efficacy [lm/W]:	109	Net weight [kg]:	2.300
Diffuser type:	OPAL	Gross weight [kg]:	2.500
Supply voltage [V]:	220-240	Index:	065880
Dimensions (H/W/T/S) [mm]:	365/114	Flicker procent:	40
Frequency [Hz]:	50 - 60	EAN:	5905963065880
Energy efficiency class:	E	Category type:	bulkheads
Source luminous flux [lm]*:	2350	CE certificate:	395/2023
Electrical protection class:	I	Version:	365
Colour rendering index:	>80	LED lifespan L70B50 [h]:	94 000
SDCM:	≤ 4	Warranty [years]:	5
Power factor:	0.90	LED lifespan L80B20 [h]:	60 000
Beam angle [°]:	120	LED lifespan L90B10 [h]:	29 000
Diffuser material:	glass	ETIM class:	EC002892
Diffuser colour:	white	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Material of the body:	Galvanized steel	Manual:	Download PDF
Colour of the body:	grey	Plik LDT:	Pobierz

Card creation date: 06 December 2018

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 395/2023