

SKVER S A 2350LM 840 MLS IP66 II CL. 1DIM B 0 (19W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	435164
Ingress protection:	IP66
Impact resistance:	IK10
Rated power of the luminaire [W]*:	19
Luminous flux [lm]*:	2350
Colour temperature [K]:	4000
Colour rendering index:	80
Electrical protection class:	II
Optics:	no
Control:	Yes + 5-stage power reduction

CHARACTERISTICS

Skver LED is the new generation of LED park and urban luminaires. It utilizes directional multi-lens arrays made of PMMA, each lens having the same optics, ensuring consistent light characteristics over time. The luminaire's design ensures the tightness of the internal chamber. As standard, the luminaire offers tool-free access to the electrical equipment using two independent knobs, which, upon request and for protection against vandalism or unauthorized opening, can be permanently secured with screws. The upper part of the luminaire features a dedicated hinge. The luminaire allows for the replacement of the integrated internal power/lighting module (compliant with ZhagaBook 13 and ZhagaBook 15 standards) without the use of tools, enabling quick and convenient servicing, allowing for the exchange of one integrated component without dismantling the entire luminaire and making soldered or screwed connections. There is no need for servicing at the installation site. Simply replace the module with a spare (accessory), close the luminaire, and then carry out the servicing work at the service location: at the luminaire owner's facility or return it to the manufacturer's service. The body and bracket are made of pressure die-cast aluminum, powder-coated in black, characterized by a very high degree of IP66 tightness and IK10 mechanical impact resistance. Standard equipment: protection against accidental luminaire overheating NTC; fully programmable DALI driver; available constant light output maintenance functions over time CLO and autonomous, 5-step power reduction; connection terminals; tool-free access. Additional options: accessory canopies transforming the external appearance of the luminaire, Zhaga connector (ZhagaBook 18); compatibility with control systems, anti-vandal protection with screws; additional SP10kV protection outside the power supply, on/off power supply without power reduction; knife switch disconnecting the integrated module voltage in case of chamber opening; made with a wire terminated with a quick connector; painting in any color from the RAL palette. Certificates: CE, RoHS, ENEC, ENEC+, Zhaga-D4i.

APPLICATION

External areas of places such as: town halls, libraries, city offices, healthcare facilities, schools, preschools, public gardens, streets, sidewalks, recreational areas: sports fields, playgrounds, bike paths, historical sites, old towns.

SKVER S A 2350LM 840 MLS IP66 II CL. 1DIM B 0 (19W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	435164	Optics:	no
EAN:	5905963435164	Material of the body:	powder coated aluminium
Category type:	street lighting	Colour of the body:	black
Light source:	LED module	Impact resistance:	IK10
Rated power of the luminaire [W]:	19	Ingress protection:	IP66
Supply voltage [V]:	220 - 240	Mounting version:	szczytowy
Frequency [Hz]:	50 - 60	Lateral surface (SCx) [m2]:	0.086
Luminous flux [lm]:	2350	Working temperature [°C]:	from -40 to +50
Luminous efficacy [lm/W]:	124	Control:	Yes + 5-stage power reduction
Energy efficiency class:	D	Protection type:	Opcja
Electrical protection class:	II	Net weight [kg]:	5.560
Colour temperature [K]:	4000	Wire type:	HO7 RNF-2x1
Colour rendering index:	80	ENEC Certificate:	0351/ENEC/24; 0121/ENEC+/24
SDCM:	≤ 4	CE certificate:	49/2024
Diffuser material:	PC	Zhaga-D4i:	ZG430121062024
Diffuser type:	transparent	Manual:	Download PDF
Version:	A	ETIM class:	EC000062

LIGHT CURVES



SKVER S A 2350LM 840 MLS IP66 II CL. 1DIM B 0 (19W)

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
435478	SKVER adapter fi 60mm

Card creation date: 03 July 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 49/2024



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl