

SKVER S L 2725 LM 830 RM7 IP66 II CL. DALI ZG B 0 (19W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	435348
Ingress protection:	IP66
Impact resistance:	IK10
Rated power of the luminaire [W]*:	19
Luminous flux [lm]*:	2725
Colour temperature [K]:	3000
Colour rendering index:	80
Electrical protection class:	II
Optics:	RM7
Control:	1

CHARACTERISTICS

Skver LED is the new generation of LED park and urban luminaires. It utilizes directional multi-lens arrays made of PMMA, each lens having the same optics, ensuring consistent light characteristics over time. The luminaire's design ensures the tightness of the internal chamber. As standard, the luminaire offers tool-free access to the electrical equipment using two independent knobs, which, upon request and for protection against vandalism or unauthorized opening, can be permanently secured with screws. The upper part of the luminaire features a dedicated hinge. The luminaire allows for the replacement of the integrated internal power/lighting module (compliant with ZhagaBook 13 and ZhagaBook 15 standards) without the use of tools, enabling quick and convenient servicing, allowing for the exchange of one integrated component without dismantling the entire luminaire and making soldered or screwed connections. There is no need for servicing at the installation site. Simply replace the module with a spare (accessory), close the luminaire, and then carry out the servicing work at the service location: at the luminaire owner's facility or return it to the manufacturer's service. The body and bracket are made of pressure die-cast aluminum, powder-coated in black, characterized by a very high degree of IP66 tightness and IK10 mechanical impact resistance. Standard equipment: protection against accidental luminaire overheating NTC; fully programmable DALI driver; available constant light output maintenance functions over time CLO and autonomous, 5-step power reduction; connection terminals; tool-free access. Additional options: accessory canopies transforming the external appearance of the luminaire, Zhaga connector (ZhagaBook 18); compatibility with control systems, anti-vandal protection with screws; additional SP10kV protection outside the power supply, on/off power supply without power reduction; knife switch disconnecting the integrated module voltage in case of chamber opening; made with a wire terminated with a quick connector; painting in any color from the RAL palette. Certificates: CE, RoHS, ENEC, ENEC+, Zhaga-D4i.

APPLICATION

External areas of places such as: town halls, libraries, city offices, healthcare facilities, schools, preschools, public gardens, streets, sidewalks, recreational areas: sports fields, playgrounds, bike paths, historical sites, old towns.


SKVER S L 2725 LM 830 RM7 IP66 II CL. DALI ZG B 0 (19W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	435348	Ingress protection:	IP66
EAN:	5905963435348	Mounting version:	szczytowy
Category type:	street lighting	Lateral surface (SCx) [m2]:	0.086
Light source:	LED module	Working temperature [°C]:	from -40 to +50
Rated power of the luminaire [W]:	19	DIMM DALI:	yes
Supply voltage [V]:	220 - 240	Control:	1
Frequency [Hz]:	50 - 60	Protection type:	Option
Luminous flux [lm]:	2725	Net weight [kg]:	5.560
Luminous efficacy [lm/W]:	143	Wire type:	HO7 RNF-2x1
Energy efficiency class:	D	Sockets:	1
Electrical protection class:	II	ETIM class:	EC000062
Colour temperature [K]:	3000	Socket type:	ZHAGA
Colour rendering index:	80	LED lifespan L90B10 [h]:	100000
SDCM:	≤ 4	Product line:	Lampy parkowe
Diffuser material:	PC	Dimensions (H/W/T/S) [mm]:	427/360/360
Diffuser type:	transparent	Mounting dimensions [mm]:	76/60/48
Version:	L	Environmental Product Declaration (EPD):	683/2024
Optics:	RM7	ENEC Certificate:	0351/ENEC/24; 0121/ENEC+/24/M1
Exchangeable source:	yes	CE certificate:	49/2024
Material of the body:	aluminium	Zhaga-D4i:	ZG430121062024
Colour of the body:	black	Manual:	Download PDF
Impact resistance:	IK10		

LIGHT CURVES



SKVER S L 2725 LM 830 RM7 IP66 II CL. DALI ZG B 0 (19W)

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
435478	SKVER adapter fi 60mm
435515	SKVER Backshield RAL9005
435522	SKVER Hood example 1 RAL9005



SKVER Backshield RAL9005 (435515)



SKVER Hood example 1
RAL9005 (435522)

Card creation date: 21 October 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 49/2024