

SKVER S L 6700 LM 840 RM7 IP66 II CL. DALI ZG B 0 (50W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	435454
Ingress protection:	IP66
Impact resistance:	IK10
Rated power of the luminaire [W]*:	50
Luminous flux [lm]*:	6650
Colour temperature [K]:	4000
Colour rendering index:	80
Electrical protection class:	II
Optics:	RM7
Control:	Yes + 5-stage power reduction

CHARACTERISTICS

SKVER LED is the new generation of LED park and urban luminaires. It utilizes directional multi-lens arrays made of PMMA, each lens having the same optics, ensuring consistent light characteristics over time. The luminaire's design ensures the tightness of the internal chamber. As standard, the luminaire offers tool-free access to the electrical equipment using two independent knobs, which, upon request and for protection against vandalism or unauthorized opening, can be permanently secured with screws. The upper part of the luminaire features a dedicated hinge. The luminaire allows for the replacement of the integrated internal power/lighting module (compliant with ZhagaBook 13 and ZhagaBook 15 standards) without the use of tools, enabling quick and convenient servicing, allowing for the exchange of one integrated component without dismantling the entire luminaire and making soldered or screwed connections. There is no need for servicing at the installation site. Simply replace the module with a spare (accessory), close the luminaire, and then carry out the servicing work at the service location: at the luminaire owner's facility or return it to the manufacturer's service. The body and bracket are made of pressure die-cast aluminum, powder-coated in black, characterized by a very high degree of IP66 tightness and IK10 mechanical impact resistance. Standard equipment: protection against accidental luminaire overheating NTC; fully programmable DALI driver; available constant light output maintenance functions over time CLO and autonomous, 5-step power reduction; connection terminals; tool-free access. Additional options: accessory canopies transforming the external appearance of the luminaire, Zhaga connector (ZhagaBook 18); compatibility with control systems, anti-vandal protection with screws; additional SP10kV protection outside the power supply, on/off power supply without power reduction; knife switch disconnecting the integrated module voltage in case of chamber opening; made with a wire terminated with a quick connector; painting in any color from the RAL palette. Certificates: CE, RoHS, ENEC, ENEC+, Zhaga D4i.

APPLICATION

External areas of places such as: town halls, libraries, city offices, healthcare facilities, schools, preschools, public gardens, streets, sidewalks, recreational areas: sports fields, playgrounds, bike paths, historical sites, old towns.


SKVER S L 6700 LM 840 RM7 IP66 II CL. DALI ZG B 0 (50W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	435454	Material of the body:	powder coated aluminium
EAN:	5905963435454	Colour of the body:	black
Category type:	street lighting	Impact resistance:	IK10
Light source:	LED module	Ingress protection:	IP66
Rated power of the luminaire [W]:	50	Mounting version:	szczytowy
Supply voltage [V]:	220 - 240	Lateral surface (SCx) [m2]:	0.086
Frequency [Hz]:	50 - 60	Working temperature [°C]:	from -40 to +50
Luminous flux [lm]:	6650	DIMM DALI:	yes
Luminous efficacy [lm/W]:	133	Control:	Yes + 5-stage power reduction
Energy efficiency class:	D	Protection type:	Opcja
Electrical protection class:	II	Net weight [kg]:	5.650
Colour temperature [K]:	4000	Wire type:	HO7 RNF-2x1
Colour rendering index:	80	ENEC Certificate:	0351/ENEC/24; 0121/ENEC+/24
SDCM:	≤ 4	CE certificate:	49/2024
Diffuser material:	PC	Manual:	Download PDF
Diffuser type:	transparent	Sockets:	1
Version:	L	ETIM class:	EC000062
Optics:	RM7	Socket type:	ZHAGA
Exchangeable source:	yes		

LIGHT CURVES



Card creation date: 21 June 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 49/2024



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl