

# TYTAN 2 LED LENS 1150MM 8800LM 840 IP66 MW 53W

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Index:</b>	593086
<b>Ingress protection:</b>	IP66
<b>Impact resistance:</b>	IK09
<b>Luminous flux [lm]*:</b>	8800
<b>Colour temperature [K]:</b>	4000
<b>Material of the body:</b>	PC
<b>Colour of the body:</b>	grey
<b>Diffuser material:</b>	PC
<b>Diffuser type:</b>	MAT
<b>Optics material:</b>	PC

## CHARACTERISTICS

The Tytan 2 LED Lens is a luminaire from the NEXT GEN line representing a new generation of luminaires dedicated to LED technology. Designed from the ground up, it introduces new solutions to improve light distribution and temperature balance. Diodes from a renowned manufacturer and new LED modules contribute to the highest luminous efficiency. This ensures that the required lighting levels are achieved and energy savings of up to 68% are achieved. The luminaire uses the solution of integrating the diffuser with the LED module and dedicated lenses. The luminaire has a number of improvements to make installation easier and faster: a diffuser suspension system, adjustable brackets to ensure an installation tolerance of +/-50 mm. It is fitted with heavy-duty stainless steel (INOX) clips as standard. The lamp body and diffuser are UV resistant.

The luminaire in Tytan 2 LED Lens is available in three versions:  
**SW** - standard wide type distribution (conventional angle 70D) with a wide range of applications including industrial halls, warehouse halls, workshops. It provides high luminous efficiency and helps to meet the most stringent guidelines of the PN-EN 12464-1 standard in terms of illuminance and high uniformity while maintaining the glare index requirements UGR19, UGR22, UGR25. Dedicated luminaire mounting height: 5,0-9,0m.  
**MW** - distribution type medium wide (conventional angle 85D) with a wide range of applications including industrial halls, warehouses, workshops. Ensures high luminous efficiency and helps to meet the most stringent PN-EN 12464-1 guidelines for illuminance and high uniformity while maintaining the glare index requirements UGR19, UGR22, UGR25. Dedicated luminaire mounting height: 3,0-7,0m.  
**VW** - very wide type distribution (conventional angle 100D) with a wide range of applications including low production rooms, low warehouses, workshops, technical rooms. Provides high luminous efficiency and helps to meet the most stringent guidelines of the PN-EN 12464-1 standard in terms of illuminance and high uniformity while maintaining the glare index requirements UGR22, UGR25. Dedicated luminaire mounting height: 2,5-5,0m.

## APPLICATION

The multifunctional LED lamp is designed for use in areas with high requirements for dust and water resistance. Especially recommended for lighting public facilities, including hospitals, educational facilities, halls, garages, passages, warehouses, shops, food industry, commercial and industrial facilities (factories, laboratories), warehouses, parking lots (underground and multi-level), sports stadiums, transport terminals and underground passages. The luminaire is ideal for new lighting applications as well as replacing traditional fluorescent luminaires with energy-saving LED solutions. Its design is adapted for surface and suspended mounting.


# TYTAN 2 LED LENS 1150MM 8800LM 840 IP66 MW 53W

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Rated power of the luminaire [W]:	53	LED lifespan L90B10 [h]:	42500
Index:	593086	Surge protection [kV]:	1
Colour temperature [K]:	4000	Diffuser material:	PC
EAN:	5905963593086	Diffuser type:	MAT
Luminous flux [lm]:	8800	Optics material:	PC
Light source:	LED module	Material of the body:	PC
Beam angle [°]:	85	Dimensions (H/W/T/S) [mm]:	1152/85/80
Light distribution type:	MW	Colour of the body:	grey
Supply voltage [V]:	220 - 240	Mounting dimensions [mm]:	800
Frequency [Hz]:	50-60	Impact resistance:	IK09
Luminous efficacy [lm/W]:	166	Ingress protection:	IP66
UGR (4H8H):	22	Mounting version:	surface, suspended
Energy efficiency class:	B	Working temperature [°C]:	from -20 to +35
Electrical protection class:	I	Number on the palette [pcs]:	100
Colour rendering index:	>80	Net weight [kg]:	1.520
SDCM:	≤ 3	Warranty [years]:	5
LED lifespan L70B50 [h]:	150000	CE certificate:	<a href="#">52/2024</a>
LED lifespan L80B20 [h]:	93000	Manual:	<a href="#">Download PDF</a>
		Photobiological safety:	RG0 - exempt (no photobiological hazard)

## LIGHT CURVES



# TYTAN 2 LED LENS 1150MM 8800LM 840 IP66 MW 53W

DETAILED CARD

## ACCESSORIES AVAILABLE

index	Name
908200	TYTAN LED. ATLAS LED. INDUSTRY LED - adjustable handle (set of 2)
60000006	M16 stuffing box plug various PA black M-16 - BPM-21



TYTAN LED. ATLAS LED. INDUSTRY LED - adjustable handle (set of 2) (908200)



M16 stuffing box plug various PA black M-16 - BPM-21 (60000006)

Card creation date: 20 June 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 52/2024