TYTAN 2 LED LENS 1150MM 4300LM 840 IP66 DALI VW 26W

DETAILED CARD





TECHNICAL PARAMETERS

Index:	593253
Ingress protection:	IP66
Impact resistance:	IK09
Luminous flux [lm]*:	4300
Colour temperature [K]:	4000
Material of the body:	PC
Colour of the body:	grey
Diffuser material:	PC
Diffuser type:	matt
Optics material:	PC

CHARACTERISTICS

The Tytan 2 LED Lens is a luminaire from the NEXT GEN line representing a new generation of luminaires dedicated to LED technology. Designed from the ground up, it introduces new solutions to improve light distribution and temperature balance. Diodes from a renowned manufacturer and new LED modules contribute to the highest luminous efficiency. This ensures that the required lighting levels are achieved and energy savings of up to 68% are achieved. The luminaire uses the solution of integrating the diffuser with the LED module and dedicated lenses. The luminaire has a number of improvements to make installation easier and faster: a diffuser suspension system, adjustable brackets to ensure an installation tolerance of ± 1.5 0 mm. It is fitted with heavy-duty stainless steel (INOX) clips as standard. The lamp body and diffuser are UV resistant.

The luminaire in Tytan 2 LED Lens is available in three versions: **SW** - standard wide type distribution(conventional angle 70D) with a wide range of applications including industrial halls, warehouse halls, workshops. It provides high luminous applications including industrial halls, warehouse rinds, workshops. It provides high full industrial reflections of the PN-EN 12464-1 standard in terms of illuminance and high uniformity while maintaining the glare index requirements UGR19, UGR22, UGR25. Dedicated luminaire mounting height: 5,0-9,0m. **MW** - distribution type medium wide (conventional angle 85D) with a wide range of applications including industrial halls, warehouses, workshops. Ensures high luminous

applications including industrial halls, warehouses, workshops. Ensures high luminoon efficiency and helps to meet the most stringent PN-EN 12464-1 guidelines for illuminance and high uniformity while maintaining the glare index requirements UGR19, UGR22, UGR25. Dedicated luminaire mounting height: 3,0-7,0m.

WW - very wide type distribution (conventional angle 100D) with a wide range of applications in the lidited between the conventional angle 100D) with a wide range of applications.

including low production rooms, low warehouses, workshops, technical rooms, Provides high luminous efficiency and helps to meet the most stringent guidelines of the PN-EN 12464-1 standard in terms of illuminance and high uniformity while maintaining the glare index requirements UGR22, UGR25. Dedicated luminaire mounting height: 2,5-5,0m.

APPLICATION

The multifunctional LED lamp is designed for use in areas with high requirements for dust and water resistance. Especially recommended for lighting public facilities, including hospitals, educational facilities, halls, garages, passages, warehouses, shops, food industry, commercial and industrial facilities (factories, laboratories), warehouses, parking lots (underground and multi-level), sports stadiums, transport terminals and underground passages. The luminaire is ideal for new lighting applications as well as replacing traditional fluorescent luminaires with energy-saving LED solutions. Its design is adapted for surface and suspended mounting. and suspended mounting.



TYTAN 2 LED LENS 1150MM 4300LM 840 IP66 DALI VW 26W


DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index: 593253 5905963593253 Light source: LED module Rated power of the luminaire [W]: 26 Luminous flux [Im]: 4300 Supply voltage [V]: 220 - 240 Frequency [Hz]: 50-60 Luminous efficacy [Im/W]: 165 Energy efficiency class: B Electrical protection class: I Colour temperature [K]: 4000 Color rendering index (Ra) >: 3 SDCM: 3 LED lifespan L70B50 [h]: 155000
Light source: Rated power of the luminaire [W]: Luminous flux [Im]: Supply voltage [V]: Frequency [Hz]: Luminous efficacy [Im/W]: Energy efficiency class: Electrical protection class: Colour temperature [K]: Color rendering index (Ra) >: SDCM: LED module 26 B Electrical 4300 50-60 Light Source B Electrical protection class: I Colour temperature [K]: 4000 SDCM: 3
Rated power of the luminaire [W]: Luminous flux [Im]: Supply voltage [V]: Frequency [Hz]: Luminous efficacy [Im/W]: Energy efficiency class: Electrical protection class: Colour temperature [K]: Color rendering index (Ra) >: SDCM: 220 - 240 50-60 165 B I Color sendering index (Ra) >: 80 SDCM:
Luminous flux [Im]: Supply voltage [V]: Frequency [Hz]: Luminous efficacy [Im/W]: Energy efficiency class: Electrical protection class: Colour temperature [K]: Color rendering index (Ra) >: SDCM: 4300 220 - 240 50-60 165 B Electrical protection class: I Colour temperature [K]: 4000 3
Supply voltage [V]: 220 - 240 Frequency [Hz]: 50-60 Luminous efficacy [Im/W]: 165 Energy efficiency class: B Electrical protection class: I Colour temperature [K]: 4000 Color rendering index (Ra) >: 80 SDCM: 3
Frequency [Hz]: 50-60 Luminous efficacy [Im/W]: 165 Energy efficiency class: B Electrical protection class: I Colour temperature [K]: 4000 Color rendering index (Ra) >: 80 SDCM: 3
Luminous efficacy [lm/W]: Energy efficiency class: Electrical protection class: Colour temperature [K]: Color rendering index (Ra) >: SDCM: 165 B 4000 80 3
Energy efficiency class: Electrical protection class: Colour temperature [K]: Color rendering index (Ra) >: 80 SDCM:
Electrical protection class: Colour temperature [K]: Color rendering index (Ra) >: SDCM: I 4000 80 3
Colour temperature [K]: 4000 Color rendering index (Ra) >: 80 SDCM: 3
Color rendering index (Ra) >: 80 SDCM: 3
SDCM: 3
I ED lifespan I 70R50 [h]: 155000
LED Mespair L70000 [n].
LED lifespan L80B20 [h]: 98000
LED lifespan L90B10 [h]: 47500
Beam angle [°]: 100
Surge protection [kV]:
Diffuser material: PC
Diffuser type: matt

Optics material:	PC
Material of the body:	PC
Colour of the body:	grey
Dimensions (H/W/T/S) [mm]:	1152/85/80
Mounting dimensions [mm]:	800
Impact resistance:	IK09
Ingress protection:	IP66
Mounting version:	surface, suspended
Working temperature [°C]:	from -20 to +35
DIMM DALI:	yes
UGR (4H8H):	21.1
Number on the palette [pcs]:	100
Net weight [kg]:	1.520
Light distribution type:	VW
Warranty [years]:	5
CE certificate:	<u>52/2024</u>
Manual:	Download PDF
Photobiological safety:	RG0 - exempt (no photobiological hazard)
Plik LDT:	Download

LIGHT CURVES



TYTAN 2 LED LENS 1150MM 4300LM 840 IP66 DALI VW 26W

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
908200	TYTAN LED. ATLAS LED. INDUSTRY LED - adjustable handle (set of 2)
6000006	M16 stuffing box plug various PA black M-16 - BPM-21







M16 stuffing box plug various PA black M-16 - BPM-21 (6000006)

