

GAMMA LED 280 1500LM 840 IP54 II CL. PIR SIDE OPAL (13W) 280MM

DETAILED CARD



TECHNICAL PARAMETERS

Index:	191183
Ingress protection:	IP54
Impact resistance:	IK10
Nominal power [W]:	13
Luminous flux [lm]*:	1500
Colour temperature [K]:	4000
SDCM:	≤ 5
Energy efficiency class:	F
Material of the body:	PP
Diffuser material:	PC

CHARACTERISTICS

The surface-mounted circular LED plafond luminaire with integrated energy-efficient LED panel is distinguished by its high luminous efficacy and increased IP54 sealing. The base and diffuser made of impact-resistant PC allow the luminaire to maintain its high IK10 impact resistance.

APPLICATION

A surface-mounted luminaire for ceiling or wall mounting, it is designed for both internal use - in rooms with increased humidity, passageways, and staircases - and external use as façade lighting. It is particularly recommended for public buildings and multi-family residential buildings.

The luminaire is intended for indoor traffic zones covered by table 5.1 of EN12464.


GAMMA LED 280 1500LM 840 IP54 II CL. PIR SIDE OPAL (13W) 280MM

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	191183	Diffuser colour:	white
EAN:	5905963191183	Optics material:	PC
Light source:	LED module	Material of the body:	PP
Nominal power [W]:	13	Colour of the body:	white
Rated power of the luminaire [W]:	18	Dimensions (H/W/T/S) [mm]:	ø280/72
Supply voltage [V]:	220-240	Mounting dimensions [mm]:	160
Frequency [Hz]:	50 - 60	Impact resistance:	IK10
Luminous flux [lm]:	1500	Ingress protection:	IP54
Luminous efficacy [lm/W]:	83	Mounting version:	surface
Energy efficiency class:	F	Working temperature [°C]:	from -20 to +25
Electrical protection class:	II	Dimensions of single box [mm]:	280/75/280
Colour temperature [K]:	4000	Net weight [kg]:	0.430
Colour rendering index:	>80	Category type:	bulkheads
SDCM:	≤ 5	Version:	280
Power factor:	0.90	Light distribution type:	open space
LED lifespan L70B50 [h]:	90000	Photobiological safety:	RG0 - exempt (no photobiological hazard)
Beam angle [°]:	120	PIR:	yes
Surge protection [kV]:	1	Warranty [years]:	5
Diffuser material:	PC	CE certificate:	102/2021
Diffuser type:	OPAL	Manual:	Download PDF

LIGHT CURVES



Card creation date: 06 June 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 102/2021



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl