

DOT CS 1W 3H NM AT WITH HEATER FOR NEGATIVE TEMPERATURES

DETAILED CARD



TECHNICAL PARAMETERS

Ingress protection:	IP65
Nominal power [W]:	1
Luminous flux [lm]*:	130
Colour temperature [K]:	5000
Electrical protection class:	II
Material of the body:	PC
Mounting version:	surface
CNBOP certificate:	4958/2023
Warranty [years]:	2 / 0.5 (bateria)
Energy efficiency class:	D

CHARACTERISTICS

Surface-mounted autonomous emergency luminaire with integrated, energy-saving LED light panel. Body made of polycarbonate (PC). Optical system available in 3 variants: basic, corridor, open space. Luminaire is fitted with batteries with 1h, 2h or 3h emergency operation time. The luminaire is using Ni-Mh or Ni-Cd battery with voltage of 3.6V and 24 hours of full charge with manual or automatic test function (AT).


APPLICATION

Autonomous emergency luminaire is mainly used for illumination of escape routes and fire protection devices after power failure, i.e. in emergency mode. Especially recommended everywhere, where it is necessary to install emergency lighting within the scope of modernization of existing system. Successfully replaces luminaires with embedded emergency module. Due to additional sealing, the luminaire achieves IP65 tightness and may be used in places with increased humidity or outdoors under the roofing.

TECHNICAL PARAMETERS TABLE

Light source:	LED module	Ingress protection:	IP65
Nominal power [W]:	1	Impact resistance:	IK07
Rated power of the luminaire [W]:	1	Mounting version:	surface
Supply voltage [V]:	220-240	Working temperature [°C]:	from -19 to +35
Frequency [Hz]:	50-60	Emergency lighting [h]:	3
Luminous flux [lm]:	130	Index:	551154
Luminous efficacy [lm/W]:	134	EAN:	5905963551154
Electrical protection class:	II	Category type:	emergency lighting
Colour temperature [K]:	5000	Version:	general
Colour rendering index:	70	Autotest:	yes
LED lifespan L70B50 [h]:	275000	Operating mode:	NM
Beam angle [°]:	120	Light distribution type:	general
Battery:	NiMh	Photobiological safety:	RG0 - exempt (no photobiological hazard)
Diffuser material:	PMMA	Luminaire rated power Omin [W]:	1
Material of the body:	PC	Energy efficiency class:	D
Colour of the body:	white	Warranty [years]:	2 / 0.5 (bateria)
Dimensions (H/W/T/S) [mm]:	ø140/40	CE certificate:	112/2023
Mounting dimensions [mm]:	104	Manual:	Download PDF

LIGHT CURVES



ACCESSORIES AVAILABLE

index	Name
545672	DOT CS galvanized steel arm
551161	Ceiling spacer DOT white matt



DOT CS galvanized steel arm (545672)



Ceiling spacer DOT white matt (551161)