

LINEA S LED SINGLE 1176MM 6300LM LS2 840 IP40 SW DALI (40W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	758201
Ingress protection:	IP40
Impact resistance:	IK03
Luminous flux [lm]*:	6300
Colour temperature [K]:	4000
Energy efficiency class:	B
Material of the body:	galvanized coated steel
Colour of the body:	RAL9010
Diffuser material:	PC
Diffuser type:	matrix led

CHARACTERISTICS

Linea S LED Single IP40 is a surface-mounted and pendant version of a single lamp in LED technology created on the basis of the LINEA S LED light line, from which it draws the latest technologies used in industrial lighting. The design used makes it possible to replace light modules and power supplies. The body, made of coated steel, provides the lamp with strength and robustness, while the narrow side profile allows installation in hard-to-reach places. Diodes from a renowned manufacturer and new LED modules contribute to the very high luminous efficacy. Versions with through-wiring available.

Attention!

The suspension should be selected separately, as an accessory, depending on the intended installation method.
Each fixture includes 2 surface-mounted brackets with a triangular element for installing the selected pendant.
Surface mounting does not require the selection of mounting accessories.

APPLICATION

A versatile LED lamp for indoor use, particularly suitable for lighting large-scale commercial, manufacturing and warehouse facilities. A lamp for use in both new applications and replacing traditional T8 and T5 luminaires with energy-efficient LED solutions.


LINEA S LED SINGLE 1176MM 6300LM LS2 840 IP40 SW DALI (40W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	758201	Colour of the body:	RAL9010
EAN:	5905963758201	Dimensions (H/W/T/S) [mm]:	1181/60/50
Light source:	LED	Impact resistance:	IK03
Rated power of the luminaire [W]:	40	Ingress protection:	IP40
Supply voltage [V]:	220-240	Mounting version:	surface, suspended
Frequency [Hz]:	50-60	DIMM DALI:	yes
Luminous flux [lm]:	6300	Through wiring:	LS2
Luminous efficacy [lm/W]:	158	Number on the palette [pcs]:	132
Energy efficiency class:	B	Net weight [kg]:	2.100
Electrical protection class:	I	AC voltage range [V]:	198-264
Colour temperature [K]:	4000	DC voltage range [V]:	176-280
Colour rendering index:	80	Working temperature [°C]:	from -20 to +35
LED lifespan L70B50 [h]:	150000	Light distribution type:	SW
LED lifespan L80B20 [h]:	100000	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
LED lifespan L90B10 [h]:	45000	Warranty [years]:	5
Beam angle [°]:	80	CE certificate:	57/2024
Surge protection [kV]:	1	ENEC Certificate:	0331/ENEC/23
Diffuser material:	PC	HACCP:	852/2004
Diffuser type:	matrix led	Manual:	Download PDF
Material of the body:	galvanized coated steel	Plik LDT:	Download

LIGHT CURVES



Card creation date: 01 August 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 57/2024

 **LENA**
LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl