LINEA S LED SINGLE 1490MM 7250LM LS2 840 IP40 105D (49W)

DETAILED CARD





TECHNICAL PARAMETERS

Index: 759406

Ingress protection: IP40

Impact resistance: IK03

Luminous flux [lm]*: 7250

Colour temperature [K]: 4000

Energy efficiency class:

Material of the body: galvanized coated steel

Colour of the body: RAL9010

Diffuser material: PC

Diffuser type: matrix led

CHARACTERISTICS

Linea S LED Single IP40 is a surface-mounted and pendant version of a single lamp in LED technology created on the basis of the LINEA S LED light line, from which it draws the latest technologies used in industrial lighting. The design used makes it possible to replace light modules and power supplies. The body, made of coated steel, provides the lamp with strength and robustness, while the narrow side profile allows installation in hard-to-reach places. Diodes from a renowned manufacturer and new LED modules contribute to the very high luminous efficacy. Versions with through-wiring available.

Attention!

The suspension should be selected separately, as an accessory, depending on the intended installation method.

Each fixture includes 2 surface-mounted brackets with a triangular element for installing the selected pendant.

Surface mounting does not require the selection of mounting accessories.

APPLICATION

A versatile LED lamp for indoor use, particularly suitable for lighting large-scale commercial, manufacturing and warehouse facilities. A lamp for use in both new applications and replacing traditional T8 and T5 luminaires with energy-efficient LED solutions.



LINEA S LED SINGLE 1490MM 7250LM LS2 840 IP40 105D (49W)


DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	759406
EAN:	5905963759406
Light source:	LED
Rated power of the luminaire [W]:	49
Supply voltage [V]:	220-240
Frequency [Hz]:	50-60
Luminous flux [lm]:	7250
Luminous efficacy [lm/W]:	148
Energy efficiency class:	С
Electrical protection class:	1
Colour temperature [K]:	4000
Color rendering index (Ra) >:	80
LED lifespan L70B50 [h]:	150000
LED lifespan L80B20 [h]:	100000
LED lifespan L90B10 [h]:	45000
Beam angle [°]:	105
Surge protection [kV]:	2
Diffuser material:	PC
Diffuser type:	matrix led
Material of the body:	galvanized coated steel

Colour of the body:	RAL9010
Dimensions (H/W/T/S) [mm]:	1495/60/50
Impact resistance:	IK03
Ingress protection:	IP40
Mounting version:	surface, suspended
Through wiring:	LS2
Number on the palette [pcs]:	132
Net weight [kg]:	2.400
AC voltage range [V]:	198-264
DC voltage range [V]:	176-280
Working temperature [°C]:	from -20 to +35
Light distribution type:	symmetric
Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Warranty [years]:	5
CE certificate:	<u>57/2024</u>
ENEC Certificate:	0331/ENEC/23
HACCP:	852/2004
Manual:	Download PDF
Plik LDT:	Download

LIGHT CURVES



Card creation date: 01 August 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

