

LINEA S LED SINGLE 1490MM 11250LM LS1 840 IP40 MW (75W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	760389
Ingress protection:	IP40
Impact resistance:	IK03
Luminous flux [lm]*:	11250
Colour temperature [K]:	4000
Energy efficiency class:	C
Material of the body:	galvanized coated steel
Colour of the body:	RAL9010
Diffuser material:	PC
Diffuser type:	matrix led

CHARACTERISTICS

Linea S LED Single IP40 is a surface-mounted and pendant version of a single lamp in LED technology created on the basis of the LINEA S LED light line, from which it draws the latest technologies used in industrial lighting. The design used makes it possible to replace light modules and power supplies. The body, made of coated steel, provides the lamp with strength and robustness, while the narrow side profile allows installation in hard-to-reach places. Diodes from a renowned manufacturer and new LED modules contribute to the very high luminous efficacy. Versions with through-wiring available.

Attention!

The suspension should be selected separately, as an accessory, depending on the intended installation method.

Each fixture includes 2 surface-mounted brackets with a triangular element for installing the selected pendant.

Surface mounting does not require the selection of mounting accessories.

APPLICATION

A versatile LED lamp for indoor use, particularly suitable for lighting large-scale commercial, manufacturing and warehouse facilities. A lamp for use in both new applications and replacing traditional T8 and T5 luminaires with energy-efficient LED solutions.

LINEA S LED SINGLE 1490MM 11250LM LS1 840 IP40 MW (75W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	760389	Dimensions (H/W/T/S) [mm]:	1495/60/50
EAN:	5905963760389	Impact resistance:	IK03
Light source:	LED	Ingress protection:	IP40
Rated power of the luminaire [W]:	75	Mounting version:	surface, suspended
Supply voltage [V]:	220-240	Number on the palette [pcs]:	132
Frequency [Hz]:	50-60	Net weight [kg]:	2
Luminous flux [lm]:	11250	AC voltage range [V]:	198-264
Luminous efficacy [lm/W]:	150	DC voltage range [V]:	176-280
Energy efficiency class:	C	Working temperature [°C]:	from -20 to +35
Electrical protection class:	I	Light distribution type:	MW
Colour temperature [K]:	4000	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Color rendering index (Ra) >:	80	Warranty [years]:	5
LED lifespan L70B50 [h]:	150000	CE certificate:	57/2024
LED lifespan L80B10 [h]:	100000	ENEC Certificate:	0331/ENEC/23
LED lifespan L90B10 [h]:	45000	HACCP:	852/2004
Beam angle [°]:	90	Manual:	Download PDF
Surge protection [kV]:	2	Environmental Product Declaration (EPD):	852/2025
Diffuser material:	PC	Mark D:	yes
Diffuser type:	matrix led	ISO Certificates:	9001:2015, 14001:2015, 45001:2018, 50001:2018
Material of the body:	galvanized coated steel	Plik LDT:	Download
Colour of the body:	RAL9010		

LIGHT CURVES



Card creation date: 16 December 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric and electronic waste equipment regulations (WEEE).

Certificate CE - Nr: 57/2024

LENA
LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl