

# ELEGANTE SYSTEM LED E 1123MM 2400LM OPAL DALI IP44 840 (30W)

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Index:</b>	388118
<b>Ingress protection:</b>	IP44/20
<b>Impact resistance:</b>	IK04
<b>Nominal power [W]:</b>	30
<b>Luminous flux [lm]*:</b>	2400
<b>Colour temperature [K]:</b>	4000
<b>SDCM:</b>	≤ 3
<b>Energy efficiency class:</b>	F
<b>Material of the body:</b>	aluminium
<b>Colour of the body:</b>	silver

## CHARACTERISTICS

ELEGANTE LED SYSTEM is a modern office fixture designed for flush mounting. It provides a combination of high light parameters and a modern decorative effect. The optical design has been designed using an iridescent diaphragm with high permeability and uniform light distribution. Available system switches allow for the design of concealed light lines in various configurations (T, X, L). The advantage of the system's roofs is the lampshade without connections to max. length 25m.

## APPLICATION

The luminaire is dedicated for internal use. For use in office and commercial facilities, in particular in representative rooms.


# ELEGANTE SYSTEM LED E 1123MM 2400LM OPAL DALI IP44 840 (30W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Light source:	LED module	Impact resistance:	IK04
Nominal power [W]:	30	Ingress protection:	IP44/20
Rated power of the luminaire [W]:	32.72	Mounting version:	recessed
Supply voltage [V]:	220-240	Working temperature [°C]:	from -20 to +35
Frequency [Hz]:	50 - 60	DIMM DALI:	yes
Source luminous flux [lm]*:	4608	Net weight [kg]:	2.200
Luminous flux [lm]:	2400	Gross weight [kg]:	2.600
Luminous efficacy [lm/W]:	73	Index:	388118
Energy efficiency class:	F	EAN:	5905963388118
Electrical protection class:	I	Category type:	systems
Colour temperature [K]:	4000	Version:	end module
Colour rendering index:	>80	Product line:	SYSTEM 30W/15W
SDCM:	≤ 3	LED lifespan L80B20 [h]:	73000
Power factor:	0.96	LED lifespan L90B10 [h]:	36000
LED lifespan L70B50 [h]:	115000	Light distribution type:	open space
Diffuser material:	PC	Kolejność:	C
Diffuser colour:	white	ETIM class:	EC000282
Material of the body:	aluminium	CE certificate:	<a href="#">244/2023</a>
Colour of the body:	silver	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Dimensions (H/W/T/S) [mm]:	1123/90/65	Warranty [years]:	5
Mounting dimensions [mm]:	1123/55	Manual:	<a href="#">Download PDF</a>

## LIGHT CURVES



# ELEGANTE SYSTEM LED E 1123MM 2400LM OPAL DALI IP44 840 (30W)

DETAILED CARD

## ACCESSORIES AVAILABLE

index	Name
81000945	ELEGANTE LED SYSTEM - OPAL diffuser - 1 rm (max 25 rm)
388736	ELEGANTE SYSTEM LED end set
388743	ELEGANTE SYSTEM LED gniazdo 3 polowe
388750	ELEGANTE SYSTEM LED gniazdo 5 polowe
388767	ELEGANTE SYSTEM LED wtyk 3 polowy
388774	ELEGANTE SYSTEM LED wtyk 5 polowy
388729	ELEGANTE SYSTEM LED klosz PC opal co-extrusion+soft fixing part 25m



ELEGANTE SYSTEM LED gniazdo 3 polowe (388743)



ELEGANTE SYSTEM LED gniazdo 5 polowe (388750)



ELEGANTE SYSTEM LED wtyk 3 polowy (388767)



ELEGANTE SYSTEM LED wtyk 5 polowy (388774)



ELEGANTE SYSTEM LED klosz PC opal co-extrusion+soft fixing part 25m (388729)

Card creation date: 03 August 2018

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 244/2023