


# ELEGANTE SYSTEM LED S 562MM 1200LM OPAL IP44 840 (15W)

DETAILED CARD



## TECHNICAL PARAMETERS

|                                 |           |
|---------------------------------|-----------|
| <b>Index:</b>                   | 388002    |
| <b>Ingress protection:</b>      | IP44/20   |
| <b>Impact resistance:</b>       | IK04      |
| <b>Nominal power [W]:</b>       | 15        |
| <b>Luminous flux [lm]*:</b>     | 1200      |
| <b>Colour temperature [K]:</b>  | 4000      |
| <b>SDCM:</b>                    | ≤ 3       |
| <b>Energy efficiency class:</b> | G         |
| <b>Material of the body:</b>    | aluminium |
| <b>Colour of the body:</b>      | silver    |

## CHARACTERISTICS

ELEGANTE LED SYSTEM is a modern office fixture designed for flush mounting. It provides a combination of high light parameters and a modern decorative effect. The optical design has been designed using an iridescent diaphragm with high permeability and uniform light distribution. Available system switches allow for the design of concealed light lines in various configurations (T, X, L). The advantage of the system's roofs is the lampshade without connections to max. length 25m.

## APPLICATION

The luminaire is dedicated for internal use. For use in office and commercial facilities, in particular in representative rooms.


# ELEGANTE SYSTEM LED S 562MM 1200LM OPAL IP44 840 (15W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

|                                   |            |                           |   |
|-----------------------------------|------------|---------------------------|---|
| Light source:                     | LED module | Impact resistance:        | IK04  |
| Nominal power [W]:                | 15         | Ingress protection:       | IP44/20   |
| Rated power of the luminaire [W]: | 16.74      | Mounting version:         | recessed  |
| Supply voltage [V]:               | 220-240    | Working temperature [°C]: | from -20 to +35   |
| Frequency [Hz]:                   | 50 - 60    | Net weight [kg]:          | 1.400   |
| Source luminous flux [lm]*:       | 2304       | Gross weight [kg]:        | 1.700   |
| Luminous flux [lm]:               | 1200       | Index:                    | 388002  |
| Luminous efficacy [lm/W]:         | 71         | EAN:                      | 5905963388002   |
| Energy efficiency class:          | G          | Category type:            | systems   |
| Electrical protection class:      | I          | Version:                  | start module  |
| Colour temperature [K]:           | 4000       | Product line:             | SYSTEM 30W/15W  |
| Colour rendering index:           | >80        | LED lifespan L80B20 [h]:  | 73000   |
| SDCM:                             | ≤ 3        | LED lifespan L90B10 [h]:  | 36000   |
| Power factor:                     | 0.86       | Light distribution type:  | open space  |
| LED lifespan L70B50 [h]:          | 115000     | Kolejność:                | A   |
| Diffuser material:                | PC         | ETIM class:               | EC000282  |
| Diffuser colour:                  | white      | CE certificate:           | <a href="#">244/2023</a>  |
| Material of the body:             | aluminium  | Photobiological safety:   | Risk Group 1 (no photobiological hazard under normal behavioral limitation) |
| Colour of the body:               | silver     | Warranty [years]:         | 5   |
| Dimensions (H/W/T/S) [mm]:        | 562/90/65  | Manual:                   | <a href="#">Download PDF</a>  |
| Mounting dimensions [mm]:         | 562/55     |                           |   |

## LIGHT CURVES



# ELEGANTE SYSTEM LED S 562MM 1200LM OPAL IP44 840 (15W)

DETAILED CARD

## ACCESSORIES AVAILABLE

| index    | Name  |
|----------|---|
| 81000945 | ELEGANTE LED SYSTEM - OPAL diffuser - 1 rm (max 25 rm)              |
| 388736   | ELEGANTE SYSTEM LED end set   |
| 388743   | ELEGANTE SYSTEM LED gniazdo 3 polowe                                |
| 388750   | ELEGANTE SYSTEM LED gniazdo 5 polowe                                |
| 388767   | ELEGANTE SYSTEM LED wtyk 3 polowy                                   |
| 388774   | ELEGANTE SYSTEM LED wtyk 5 polowy                                   |
| 388729   | ELEGANTE SYSTEM LED klosz PC opal co-extrusion+soft fixing part 25m |



ELEGANTE SYSTEM LED gniazdo 3 polowe (388743)



ELEGANTE SYSTEM LED gniazdo 5 polowe (388750)



ELEGANTE SYSTEM LED wtyk 3 polowy (388767)



ELEGANTE SYSTEM LED wtyk 5 polowy (388774)



ELEGANTE SYSTEM LED klosz PC opal co-extrusion+soft fixing part 25m (388729)

Card creation date: 03 August 2018

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 244/2023