


ELEGANTE SYSTEM LED S 562MM 700LM OPAL IP44 840 (8W)

DETAILED CARD



TECHNICAL PARAMETERS

| | |
|---------------------------------|-----------|
| Index: | 388125 |
| Ingress protection: | IP44/20 |
| Impact resistance: | IK04 |
| Nominal power [W]: | 8 |
| Luminous flux [lm]*: | 700 |
| Colour temperature [K]: | 4000 |
| SDCM: | ≤ 3 |
| Energy efficiency class: | G |
| Material of the body: | aluminium |
| Colour of the body: | silver |

CHARACTERISTICS

ELEGANTE LED SYSTEM is a modern office fixture designed for flush mounting. It provides a combination of high light parameters and a modern decorative effect. The optical design has been designed using an iridescent diaphragm with high permeability and uniform light distribution. Available system switches allow for the design of concealed light lines in various configurations (T, X, L). The advantage of the system's roofs is the lampshade without connections to max. length 25m.

APPLICATION

The luminaire is dedicated for internal use. For use in office and commercial facilities, in particular in representative rooms.

ELEGANTE SYSTEM LED S 562MM 700LM OPAL IP44 840 (8W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

| | | | |
|-----------------------------------|--------------|---------------------------|---|
| Nominal power [W]: | 8 | Material of the body: | aluminium |
| Light source: | LED module | Colour of the body: | silver |
| Colour temperature [K]: | 4000 | Mounting dimensions [mm]: | 562/55 |
| Luminous flux [lm]: | 700 | Impact resistance: | IK04 |
| Rated power of the luminaire [W]: | 10.33 | Mounting version: | recessed |
| Supply voltage [V]: | 220-240 | Working temperature [°C]: | from -20 to +35 |
| Frequency [Hz]: | 50 - 60 | Net weight [kg]: | 1.400 |
| Version: | start module | Gross weight [kg]: | 1.700 |
| Source luminous flux [lm]*: | 1223 | Index: | 388125 |
| Dimensions (H/W/T/S) [mm]: | 562/90/65 | EAN: | 5905963388125 |
| Ingress protection: | IP44/20 | Category type: | systems |
| Luminous efficacy [lm/W]: | 67 | Product line: | SYSTEM 16W/8W |
| Energy efficiency class: | G | LED lifespan L80B20 [h]: | 73000 |
| Electrical protection class: | I | LED lifespan L90B10 [h]: | 36000 |
| Colour rendering index: | >80 | Light distribution type: | open space |
| SDCM: | ≤ 3 | Kolejność: | A |
| Power factor: | 0.75 | ETIM class: | EC000282 |
| LED lifespan L70B50 [h]: | 115000 | CE certificate: | 244/2023 |
| Diffuser material: | PC | Photobiological safety: | Risk Group 1 (no photobiological hazard under normal behavioral limitation) |
| Diffuser colour: | white | Warranty [years]: | 5 |
| | | Manual: | Download PDF |
| | | Plik LDT: | Pobierz |

ELEGANTE SYSTEM LED S 562MM 700LM OPAL IP44 840 (8W)

DETAILED CARD

ACCESSORIES AVAILABLE

| index | Name |
|----------|---|
| 81000945 | ELEGANTE LED SYSTEM - OPAL diffuser - 1 rm (max 25 rm) |
| 388736 | ELEGANTE SYSTEM LED end set |
| 388743 | ELEGANTE SYSTEM LED gniazdo 3 polowe |
| 388750 | ELEGANTE SYSTEM LED gniazdo 5 polowe |
| 388767 | ELEGANTE SYSTEM LED wtyk 3 polowy |
| 388774 | ELEGANTE SYSTEM LED wtyk 5 polowy |
| 388729 | ELEGANTE SYSTEM LED klosz PC opal co-extrusion+soft fixing part 25m |



ELEGANTE SYSTEM LED gniazdo 3 polowe (388743)



ELEGANTE SYSTEM LED gniazdo 5 polowe (388750)



ELEGANTE SYSTEM LED wtyk 3 polowy (388767)



ELEGANTE SYSTEM LED wtyk 5 polowy (388774)



ELEGANTE SYSTEM LED klosz PC opal co-extrusion+soft fixing part 25m (388729)

Card creation date: 03 August 2018

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 244/2023