

ELEGANTE LED 575MM 1200LM OPAL DALI IP44 830 (15W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	388576
Ingress protection:	IP44/20
Impact resistance:	IK02
Nominal power [W]:	15
Luminous flux [lm]*:	1200
Colour temperature [K]:	3000
SDCM:	≤ 3
Energy efficiency class:	G
Material of the body:	aluminium
Colour of the body:	silver

CHARACTERISTICS

ELEGANTE LED SYSTEM is a modern office fixture designed for flush mounting. It provides a combination of high light parameters and a modern decorative effect. The optical design has been designed using an iridescent diaphragm with high permeability and uniform light distribution.

APPLICATION

The luminaire is dedicated for internal use. For use in office and commercial facilities, in particular in representative rooms.

ELEGANTE LED 575MM 1200LM OPAL DALI IP44 830 (15W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Light source:	LED module	Impact resistance:	IK02
Nominal power [W]:	15	Ingress protection:	IP44/20
Rated power of the luminaire [W]:	17.80	Mounting version:	recessed
Supply voltage [V]:	220-240	Working temperature [°C]:	from -17 to +35
Frequency [Hz]:	50 - 60	DIMM DALI:	yes
Luminous flux [lm]:	1200	Accessories included:	diffuser
Luminous efficacy [lm/W]:	67	Net weight [kg]:	1.600
Energy efficiency class:	G	Index:	388576
Electrical protection class:	I	EAN:	5905963388576
Colour temperature [K]:	3000	Category type:	systems
Colour rendering index:	>80	Version:	individual
SDCM:	≤ 3	Product line:	INDIVIDUAL VARIANT 30W/15W
LED lifespan L70B50 [h]:	115000	LED lifespan L80B20 [h]:	73000
Diffuser material:	PC	LED lifespan L90B10 [h]:	36000
Diffuser type:	OPAL	Light distribution type:	open space
Diffuser colour:	white	ETIM class:	EC002892
Material of the body:	aluminium	CE certificate:	243/2023
Colour of the body:	silver	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Dimensions (H/W/T/S) [mm]:	575/52/66	Warranty [years]:	5
Mounting dimensions [mm]:	578/54	Manual:	Download PDF

LIGHT CURVES



ELEGANTE LED 575MM 1200LM OPAL DALI IP44 830 (15W)

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
81000945	ELEGANTE LED SYSTEM - OPAL diffuser - 1 rm (max 25 rm)
388736	ELEGANTE SYSTEM LED end set
388743	ELEGANTE SYSTEM LED gniazdo 3 polowe
388750	ELEGANTE SYSTEM LED gniazdo 5 polowe
388767	ELEGANTE SYSTEM LED wtyk 3 polowy
388774	ELEGANTE SYSTEM LED wtyk 5 polowy
388729	ELEGANTE SYSTEM LED klosz PC opal co-extrusion+soft fixing part 25m



ELEGANTE SYSTEM LED gniazdo 3 polowe (388743)



ELEGANTE SYSTEM LED gniazdo 5 polowe (388750)



ELEGANTE SYSTEM LED wtyk 3 polowy (388767)



ELEGANTE SYSTEM LED wtyk 5 polowy (388774)



ELEGANTE SYSTEM LED klosz PC opal co-extrusion+soft fixing part 25m (388729)

Card creation date: 03 August 2018

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 243/2023