

ELEGANTE LED 1136MM 1400LM OPAL DALI IP44 840 (16W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	388316
Ingress protection:	IP44/20
Impact resistance:	IK02
Nominal power [W]:	16
Luminous flux [lm]*:	1400
Colour temperature [K]:	4000
SDCM:	≤ 3
Energy efficiency class:	F
Material of the body:	aluminium
Colour of the body:	silver

CHARACTERISTICS

ELEGANTE LED SYSTEM is a modern office fixture designed for flush mounting. It provides a combination of high light parameters and a modern decorative effect. The optical design has been designed using an iridescent diaphragm with high permeability and uniform light distribution.

APPLICATION

The luminaire is dedicated for internal use. For use in office and commercial facilities, in particular in representative rooms.

ELEGANTE LED 1136MM 1400LM OPAL DALI IP44 840 (16W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Nominal power [W]:	16	Colour of the body:	silver
Light source:	LED module	Mounting dimensions [mm]:	1139/54
Colour temperature [K]:	4000	Impact resistance:	IK02
Luminous flux [lm]:	1400	Mounting version:	recessed
Rated power of the luminaire [W]:	18.20	Working temperature [°C]:	from -17 to +35
Diffuser type:	OPAL	Accessories included:	diffuser
Supply voltage [V]:	220-240	Net weight [kg]:	2.200
DIMM DALI:	1	Index:	388316
Frequency [Hz]:	50 - 60	EAN:	5905963388316
Version:	individual	Category type:	systems
Dimensions (H/W/T/S) [mm]:	1136/52/66	Product line:	INDIVIDUAL VARIANT 16W/8W
Ingress protection:	IP44/20	LED lifespan L80B20 [h]:	73000
Luminous efficacy [lm/W]:	76	LED lifespan L90B10 [h]:	36000
Energy efficiency class:	F	Light distribution type:	open space
Electrical protection class:	I	ETIM class:	EC002892
Colour rendering index:	>80	CE certificate:	243/2023
SDCM:	≤ 3	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
LED lifespan L70B50 [h]:	115000	Warranty [years]:	5
Diffuser material:	PC	Manual:	Download PDF
Diffuser colour:	white	Plik LDT:	Pobierz
Material of the body:	aluminium		

ELEGANTE LED 1136MM 1400LM OPAL DALI IP44 840 (16W)

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
81000945	ELEGANTE LED SYSTEM - OPAL diffuser - 1 rm (max 25 rm)
388736	ELEGANTE SYSTEM LED end set
388743	ELEGANTE SYSTEM LED gniazdo 3 polowe
388750	ELEGANTE SYSTEM LED gniazdo 5 polowe
388767	ELEGANTE SYSTEM LED wtyk 3 polowy
388774	ELEGANTE SYSTEM LED wtyk 5 polowy
388729	ELEGANTE SYSTEM LED klosz PC opal co-extrusion+soft fixing part 25m



ELEGANTE SYSTEM LED gniazdo 3 polowe (388743)



ELEGANTE SYSTEM LED gniazdo 5 polowe (388750)



ELEGANTE SYSTEM LED wtyk 3 polowy (388767)



ELEGANTE SYSTEM LED wtyk 5 polowy (388774)



ELEGANTE SYSTEM LED klosz PC opal co-extrusion+soft fixing part 25m (388729)

Card creation date: 03 August 2018

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 243/2023