

# ELEGANTE LED 575MM 700LM OPAL IP44 840 (8W)

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Index:</b>	388286
<b>Ingress protection:</b>	IP44/20
<b>Impact resistance:</b>	IK02
<b>Nominal power [W]:</b>	8
<b>Luminous flux [lm]*:</b>	700
<b>Colour temperature [K]:</b>	4000
<b>SDCM:</b>	≤ 3
<b>Energy efficiency class:</b>	F
<b>Material of the body:</b>	aluminium
<b>Colour of the body:</b>	silver

## CHARACTERISTICS

ELEGANTE LED SYSTEM is a modern office fixture designed for flush mounting. It provides a combination of high light parameters and a modern decorative effect. The optical design has been designed using an iridescent diaphragm with high permeability and uniform light distribution.

## APPLICATION

The luminaire is dedicated for internal use. For use in office and commercial facilities, in particular in representative rooms.

# ELEGANTE LED 575MM 700LM OPAL IP44 840 (8W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

<b>Nominal power [W]:</b>	8	<b>Colour of the body:</b>	silver
<b>Light source:</b>	LED module	<b>Mounting dimensions [mm]:</b>	578/54
<b>Colour temperature [K]:</b>	4000	<b>Impact resistance:</b>	IK02
<b>Luminous flux [lm]:</b>	700	<b>Mounting version:</b>	recessed
<b>Rated power of the luminaire [W]:</b>	9.10	<b>Working temperature [°C]:</b>	from -17 to +35
<b>Diffuser type:</b>	OPAL	<b>Accessories included:</b>	diffuser
<b>Supply voltage [V]:</b>	220-240	<b>Net weight [kg]:</b>	1.600
<b>Frequency [Hz]:</b>	50 - 60	<b>Index:</b>	388286
<b>Version:</b>	individual	<b>EAN:</b>	5905963388286
<b>Dimensions (H/W/T/S) [mm]:</b>	575/52/66	<b>Category type:</b>	systems
<b>Ingress protection:</b>	IP44/20	<b>Product line:</b>	INDIVIDUAL VARIANT 16W/8W
<b>Luminous efficacy [lm/W]:</b>	76	<b>LED lifespan L80B20 [h]:</b>	73000
<b>Energy efficiency class:</b>	F	<b>LED lifespan L90B10 [h]:</b>	36000
<b>Electrical protection class:</b>	I	<b>Light distribution type:</b>	open space
<b>Colour rendering index:</b>	>80	<b>ETIM class:</b>	EC002892
<b>SDCM:</b>	≤ 3	<b>CE certificate:</b>	<a href="#">243/2023</a>
<b>LED lifespan L70B50 [h]:</b>	115000	<b>Photobiological safety:</b>	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
<b>Diffuser material:</b>	PC	<b>Warranty [years]:</b>	5
<b>Diffuser colour:</b>	white	<b>Manual:</b>	<a href="#">Download PDF</a>
<b>Material of the body:</b>	aluminium	<b>Plik LDT:</b>	<a href="#">Pobierz</a>

# ELEGANTE LED 575MM 700LM OPAL IP44 840 (8W)

DETAILED CARD

## ACCESSORIES AVAILABLE

index	Name
81000945	ELEGANTE LED SYSTEM - OPAL diffuser - 1 rm (max 25 rm)
388736	ELEGANTE SYSTEM LED end set
388743	ELEGANTE SYSTEM LED gniazdo 3 polowe
388750	ELEGANTE SYSTEM LED gniazdo 5 polowe
388767	ELEGANTE SYSTEM LED wtyk 3 polowy
388774	ELEGANTE SYSTEM LED wtyk 5 polowy
388729	ELEGANTE SYSTEM LED klosz PC opal co-extrusion+soft fixing part 25m



ELEGANTE SYSTEM LED gniazdo 3 polowe (388743)



ELEGANTE SYSTEM LED gniazdo 5 polowe (388750)



ELEGANTE SYSTEM LED wtyk 3 polowy (388767)



ELEGANTE SYSTEM LED wtyk 5 polowy (388774)



ELEGANTE SYSTEM LED klosz PC opal co-extrusion+soft fixing part 25m (388729)

Card creation date: 03 August 2018

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 243/2023