

PORTAL EMERGENCY 250LM 20M AT IP54 1H+ SET OF 6 PICTOGRAMS + HEATING KIT

DETAILED CARD



TECHNICAL PARAMETERS

| | |
|---------------------------------|--------|
| Index: | 736735 |
| Ingress protection: | IP54 |
| Nominal power [W]: | 3 |
| Luminous flux [lm]*: | 250 |
| Colour temperature [K]: | 4000 |
| Colour rendering index: | >80 |
| SDCM: | ≤ 3 |
| Energy efficiency class: | G |
| Diffuser material: | PC |
| Diffuser type: | clear |

CHARACTERISTICS

Emergency Portal is a luminaire designed to illuminate open spaces and to indicate the direction of evacuation through the use of pictograms. A modern emergency module with an automatic test ensures maintenance-free reporting of errors or the need to replace the battery. Efficient LEDs of the latest generation ensure adequate illumination of escape routes.

APPLICATION

The high level of protection IP54 allows for use in industrial spaces, and the slender, timeless and neutral body of the luminaire will also be perfect for public facilities - offices, restaurants, commercial facilities. The possibility of ceiling and wall mounting extends the range of possible applications.

PORTAL EMERGENCY 250LM 20M AT IP54 1H+ SET OF 6 PICTOGRAMS + HEATING KIT

DETAILED CARD

TECHNICAL PARAMETERS TABLE

| | | | |
|-----------------------------------|---------------|----------------------------|------------------------------|
| Nominal power [W]: | 3 | Diffuser material: | PC |
| Index: | 736735 | Diffuser colour: | transparent |
| Colour temperature [K]: | 4000 | Optics material: | ABS |
| EAN: | 5905963736735 | Optics: | PC |
| Luminous flux [lm]: | 250 | Colour of the body: | white |
| Light source: | LED module | Dimensions (H/W/T/S) [mm]: | 280/185/55 |
| Diffuser type: | clear | Ingress protection: | IP54 |
| Rated power of the luminaire [W]: | 3 | Mounting version: | surface |
| Supply voltage [V]: | 3 | Working temperature [°C]: | od -20 do +35 |
| Frequency [Hz]: | 50-60 | Tilt angle adjustment [°]: | no |
| Luminous efficacy [lm/W]: | 88 | Net weight [kg]: | 0.730 |
| Energy efficiency class: | G | Category type: | emergency lighting |
| Electrical protection class: | II | AC voltage range [V]: | 207-253 |
| Colour rendering index: | >80 | Emergency lighting [h]: | 1 |
| SDCM: | ≤ 3 | Autotest: | yes |
| Power factor: | 0.90 | CE certificate: | 50/2023 |
| LED lifespan L70B50 [h]: | 100000 | Manual: | Download PDF |
| Beam angle [°]: | 120 | CNBOP certificate: | 5147/2023 |

Card creation date: 10 July 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 50/2023