

# LINEA S LED 3528MM IP54 11P 2C

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Index:</b>	587573
<b>Material of the body:</b>	coated sheet steel
<b>Colour of the body:</b>	RAL9010
<b>Ingress protection:</b>	IP54
<b>Mounting version:</b>	surface, suspended, modular suspended ceiling
<b>Through wiring:</b>	LS2
<b>Dimensions (H/W/T/S) [mm]:</b>	3528/67/50
<b>Impact resistance:</b>	IK03

## CHARACTERISTICS

LINEA S LED is a surface-mounted and suspended light-line system, representing a new generation of luminaires dedicated to LED technology. The innovative connection system and loop-through cabling enables the rapid assembly of luminaires into a light line and allows flexible replacement of light modules to meet current needs. The design used allows for easy assembly and power connection. The steel body, designed from the ground up, ensures the luminaire's strength and robustness, while the narrow side profile allows installation in hard-to-reach areas.

## APPLICATION

Versatile led lamp designed for indoor use, especially recommended for lighting large-scale commercial, manufacturing and warehouse facilities. The lamp for use in both new applications and replacements of traditional T8 and T5 fixtures with energy-efficient LED solutions.

# LINEA S LED 3528MM IP54 11P 2C

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

<b>Index:</b>	587573	<b>Ingress protection:</b>	IP54
<b>EAN:</b>	5905963587573	<b>Mounting version:</b>	surface, suspended, modular suspended ceiling
<b>Material of the body:</b>	coated sheet steel	<b>Working temperature [°C]:</b>	from -25 to +35
<b>Electrical protection class:</b>	I	<b>Through wiring:</b>	LS2
<b>Wire type:</b>	5x2,5+6x1,5	<b>Number on the palette [pcs]:</b>	104
<b>Remarks:</b>	Number of connectors: 2	<b>Net weight [kg]:</b>	3.250
<b>Colour of the body:</b>	RAL9010	<b>Warranty [years]:</b>	5
<b>Dimensions (H/W/T/S) [mm]:</b>	3528/67/50	<b>Accessories included:</b>	end cap IP54 LS2, end cap IP54, zawiesie, uchwyt montażowy natynkowy, maskownice metalowe, zestawy zasilające, łącznik profili LED
<b>Mounting dimensions [mm]:</b>	2650	<b>Manual:</b>	<a href="#">Download PDF</a>
<b>Impact resistance:</b>	IK03		

# LINEA S LED 3528MM IP54 11P 2C

---

DETAILED CARD

# LINEA S LED 3528MM IP54 11P 2C

DETAILED CARD

## ACCESSORIES AVAILABLE

index	Name
980077	LINEA S LED hang 3m
980084	LINEA S LED power set 5P
981388	LINEA S LED power set 11P
981173	LINEA S LED hang 1.5m
980954	Linea S LED surface mount bracket
981418	LINEA S LED pendant sm 1.5
981425	LINEA S LED chain pendant
980978	Linea S LED power set 7P
980961	LINEA S LED pendant sm 3m
592256	LINEA S LED - end cap IP54 LS2
592263	LINEA S LED - end cap IP54
592270	LINEA S LED - LED profile connector IP54
592287	LINEA S LED - connector of SUPPORT profiles IP54
592294	LINEA S LED - metal cover 584mm IP54
592300	LINEA S LED - metal cover 1172mm IP54
592317	LINEA S LED - metal cover 1760mm IP54
592362	LINEA S LED - Power connector removal tool



LINEA S LED power set 5P (980084)



LINEA S LED power set 11P (981388)



LINEA S LED hang 1.5m (981173)



Linea S LED surface mount bracket (980954)



LINEA S LED chain pendant (981425)



Linea S LED power set 7P (980978)

# LINEA S LED 3528MM IP54 11P 2C

---

DETAILED CARD

Card creation date: 18 July 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr:



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl