

# LEO PARK LED 30W 3700LM 4000K RM2

DETAILED CARD



## TECHNICAL PARAMETERS

Index:	599774
Light source:	LED module
Ingress protection:	IP65
Impact resistance:	IK07
Nominal power [W]:	30
Luminous flux [lm]*:	3700
Colour temperature [K]:	4000
Colour rendering index:	>70
Electrical protection class:	I
Energy efficiency class:	D

## CHARACTERISTICS

A modern street light characterised by minimalist design of its aluminium body. The PMMA light diffuser emits pleasant light. Thanks to the use of lens matrices (arrays), 3 light distribution versions are available:  
ASM1 – medium asymmetric – squares, car parks, parks;  
RM2 – medium street – estate roads, alleys in a park;  
SM1 – medium symmetric – squares, car parks, parks.  
Installation possible directly on a pole with end diameter of 60–65 mm.

## APPLICATION

Luminaires for lighting streets, pavements, built-up areas, parks, squares and car parks.

## DETAILS

"  
Oprawy do oświetlenia ulic, alejek w parkach.&nbsp;nbsp;


# LEO PARK LED 30W 3700LM 4000K RM2

## DETAILED CARD

### TECHNICAL PARAMETERS TABLE

Nominal power [W]:	30	Material of the body:	aluminium
Index:	599774	Colour of the body:	graphite RAL 7016
Colour temperature [K]:	4000	Dimensions (H/W/T/S) [mm]:	430/ø400
EAN:	5905963599774	Impact resistance:	IK07
Luminous flux [lm]:	3700	Ingress protection:	IP65
Light source:	LED module	Mounting version:	on the pole
Version:	RM2	Working temperature [°C]:	from -30 to +40
Rated power of the luminaire [W]:	30	Net weight [kg]:	4
Energy efficiency class:	D	Category type:	Park and city lighting
Supply voltage [V]:	220-240	Category of application:	parkings and bicycle paths
Frequency [Hz]:	50 - 60	ETIM class:	EC000062
Luminous efficacy [lm/W]:	123	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Electrical protection class:	I	CE certificate:	<a href="#">167/2020</a>
Colour rendering index:	>70	Warranty [years]:	5
LED lifespan L70B50 [h]:	100000	Manual:	<a href="#">Download PDF</a>
Diffuser material:	PMMA	Plik LDT:	<a href="#">Download</a>
Diffuser type:	transparent		

### LIGHT CURVES



Card creation date: 09 May 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 167/2020



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: [hello@lenalighting.pl](mailto:hello@lenalighting.pl), [www.lenalighting.pl](http://www.lenalighting.pl)