

LINEA S LED SINGLE 1176MM 10850LM LS1 840 IP40 SA DALI (75W)

DETAILED CARD



TECHNICAL PARAMETERS

| | |
|---------------------------------|-------------------------|
| Index: | 847868 |
| Ingress protection: | IP40 |
| Impact resistance: | IK03 |
| Luminous flux [lm]*: | 10850 |
| Colour temperature [K]: | 4000 |
| Energy efficiency class: | C |
| Material of the body: | galvanized coated steel |
| Colour of the body: | RAL9010 |
| Diffuser material: | PC |
| Diffuser type: | matrix led |

CHARACTERISTICS

Linea S LED Single IP40 is a surface-mounted and pendant version of a single lamp in LED technology created on the basis of the LINEA S LED light line, from which it draws the latest technologies used in industrial lighting. The design used makes it possible to replace light modules and power supplies. The body, made of coated steel, provides the lamp with strength and robustness, while the narrow side profile allows installation in hard-to-reach places. Diodes from a renowned manufacturer and new LED modules contribute to the very high luminous efficacy. Versions with through-wiring available.

Attention!

The suspension should be selected separately, as an accessory, depending on the intended installation method.

Each fixture includes 2 surface-mounted brackets with a triangular element for installing the selected pendant.

Surface mounting does not require the selection of mounting accessories.

APPLICATION

A versatile LED lamp for indoor use, particularly suitable for lighting large-scale commercial, manufacturing and warehouse facilities. A lamp for use in both new applications and replacing traditional T8 and T5 luminaires with energy-efficient LED solutions.

LINEA S LED SINGLE 1176MM 10850LM LS1 840 IP40 SA DALI (75W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

| | | | |
|-----------------------------------|-------------------------|--|---|
| Index: | 847868 | Dimensions (H/W/T/S) [mm]: | 1181/60/50 |
| EAN: | 5905963847868 | Impact resistance: | IK03 |
| Light source: | LED | Ingress protection: | IP40 |
| Rated power of the luminaire [W]: | 75 | Mounting version: | surface, suspended |
| Supply voltage [V]: | 220-240 | DIMM DALI: | yes |
| Frequency [Hz]: | 50-60 | Number on the palette [pcs]: | 100 |
| Luminous flux [lm]: | 10850 | Net weight [kg]: | 1.700 |
| Luminous efficacy [lm/W]: | 150 | AC voltage range [V]: | 198-264 |
| Energy efficiency class: | C | DC voltage range [V]: | 176-280 |
| Electrical protection class: | I | Working temperature [°C]: | from -20 to +35 |
| Colour temperature [K]: | 4000 | Light distribution type: | SA |
| Color rendering index (Ra) >: | 80 | Photobiological safety: | Risk Group 1 (no photobiological hazard under normal behavioral limitation) |
| LED lifespan L70B50 [h]: | 150000 | Warranty [years]: | 5 |
| LED lifespan L80B10 [h]: | 100000 | CE certificate: | 57/2024 |
| LED lifespan L90B10 [h]: | 45000 | ENEC Certificate: | 0331/ENEC/23 |
| Beam angle [°]: | asymmetric | HACCP: | 852/2004 |
| Surge protection [kV]: | 1 | Manual: | Download PDF |
| Diffuser material: | PC | Environmental Product Declaration (EPD): | 852/2025 |
| Diffuser type: | matrix led | Mark D: | yes |
| Material of the body: | galvanized coated steel | ISO Certificates: | 9001:2015, 14001:2015, 45001:2018, 50001:2018 |
| Colour of the body: | RAL9010 | Plik LDT: | Download |

LIGHT CURVES



Card creation date: 16 December 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 57/2024



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl