

LINEA S LED SINGLE 1490MM 10650LM LS1 840 IP40 DAN (75W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	850066
Ingress protection:	IP40
Impact resistance:	IK03
Luminous flux [lm]*:	10650
Colour temperature [K]:	4000
Energy efficiency class:	C
Material of the body:	galvanized coated steel
Colour of the body:	RAL9010
Diffuser material:	PC
Diffuser type:	matrix led

CHARACTERISTICS

Linea S LED Single IP40 is a surface-mounted and pendant version of a single lamp in LED technology created on the basis of the LINEA S LED light line, from which it draws the latest technologies used in industrial lighting. The design used makes it possible to replace light modules and power supplies. The body, made of coated steel, provides the lamp with strength and robustness, while the narrow side profile allows installation in hard-to-reach places. Diodes from a renowned manufacturer and new LED modules contribute to the very high luminous efficacy. Versions with through-wiring available.

Attention!

The suspension should be selected separately, as an accessory, depending on the intended installation method.
Each fixture includes 2 surface-mounted brackets with a triangular element for installing the selected pendant.
Surface mounting does not require the selection of mounting accessories.

APPLICATION

A versatile LED lamp for indoor use, particularly suitable for lighting large-scale commercial, manufacturing and warehouse facilities. A lamp for use in both new applications and replacing traditional T8 and T5 luminaires with energy-efficient LED solutions.

LINEA S LED SINGLE 1490MM 10650LM LS1 840 IP40 DAN (75W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	850066	Material of the body:	galvanized coated steel
EAN:	5905963850066	Colour of the body:	RAL9010
Light source:	LED	Dimensions (H/W/T/S) [mm]:	1495/60/50
Rated power of the luminaire [W]:	75	Impact resistance:	IK03
Supply voltage [V]:	220-240	Ingress protection:	IP40
Frequency [Hz]:	50-60	Mounting version:	surface, suspended
Luminous flux [lm]:	10650	Number on the palette [pcs]:	100
Luminous efficacy [lm/W]:	150	Net weight [kg]:	2
Energy efficiency class:	C	AC voltage range [V]:	198-264
Electrical protection class:	I	DC voltage range [V]:	176-280
Colour temperature [K]:	4000	Working temperature [°C]:	from -20 to +35
Colour rendering index:	80	Light distribution type:	DAN
LED lifespan L70B50 [h]:	150000	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
LED lifespan L80B20 [h]:	100000	Warranty [years]:	5
LED lifespan L90B10 [h]:	45000	CE certificate:	57/2024
Beam angle [°]:	butterfly	ENEC Certificate:	0331/ENEC/23
Surge protection [kV]:	2	HACCP:	852/2004
Diffuser material:	PC	Manual:	Download PDF
Diffuser type:	matrix led	Plik LDT:	Download

LIGHT CURVES

