

# LINEA S LED SINGLE 1764MM 9500LM LS2 840 IP40 SN DALI (57W)

DETAILED CARD



## TECHNICAL PARAMETERS

|                          |                         |
|--------------------------|-------------------------|
| Index:                   | 856884                  |
| Ingress protection:      | IP40                    |
| Impact resistance:       | IK03                    |
| Luminous flux [lm]*:     | 9500                    |
| Colour temperature [K]:  | 4000                    |
| Energy efficiency class: | B                       |
| Material of the body:    | galvanized coated steel |
| Colour of the body:      | RAL9010                 |
| Diffuser material:       | PC                      |
| Diffuser type:           | matrix led              |

## CHARACTERISTICS

Linea S LED Single IP40 is a surface-mounted and pendant version of a single lamp in LED technology created on the basis of the LINEA S LED light line, from which it draws the latest technologies used in industrial lighting. The design used makes it possible to replace light modules and power supplies. The body, made of coated steel, provides the lamp with strength and robustness, while the narrow side profile allows installation in hard-to-reach places. Diodes from a renowned manufacturer and new LED modules contribute to the very high luminous efficacy. Versions with through-wiring available.

### Attention!

The suspension should be selected separately, as an accessory, depending on the intended installation method.  
Each fixture includes 2 surface-mounted brackets with a triangular element for installing the selected pendant.  
Surface mounting does not require the selection of mounting accessories.

## APPLICATION

A versatile LED lamp for indoor use, particularly suitable for lighting large-scale commercial, manufacturing and warehouse facilities. A lamp for use in both new applications and replacing traditional T8 and T5 luminaires with energy-efficient LED solutions.

# LINEA S LED SINGLE 1764MM 9500LM LS2 840 IP40 SN DALI (57W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

|                                   |                         |                              |   |
|-----------------------------------|-------------------------|------------------------------|---|
| Index:                            | 856884                  | Colour of the body:          | RAL9010   |
| EAN:                              | 5905963856884           | Dimensions (H/W/T/S) [mm]:   | 1769/60/50  |
| Light source:                     | LED                     | Impact resistance:           | IK03  |
| Rated power of the luminaire [W]: | 57                      | Ingress protection:          | IP40  |
| Supply voltage [V]:               | 220-240                 | Mounting version:            | surface, suspended  |
| Frequency [Hz]:                   | 50-60                   | DIMM DALI:                   | yes   |
| Luminous flux [lm]:               | 9500                    | Through wiring:              | LS2   |
| Luminous efficacy [lm/W]:         | 169                     | Number on the palette [pcs]: | 100   |
| Energy efficiency class:          | B                       | Net weight [kg]:             | 2.900   |
| Electrical protection class:      | I                       | AC voltage range [V]:        | 198-264   |
| Colour temperature [K]:           | 4000                    | DC voltage range [V]:        | 176-280   |
| Colour rendering index:           | 80                      | Working temperature [°C]:    | from -20 to +35   |
| LED lifespan L70B50 [h]:          | 150000                  | Light distribution type:     | SN  |
| LED lifespan L80B20 [h]:          | 100000                  | Photobiological safety:      | Risk Group 1 (no photobiological hazard under normal behavioral limitation) |
| LED lifespan L90B10 [h]:          | 45000                   | Warranty [years]:            | 5   |
| Beam angle [°]:                   | 65                      | CE certificate:              | <a href="#">57/2024</a>   |
| Surge protection [kV]:            | 1                       | ENEC Certificate:            | <a href="#">0331/ENEC/23</a>  |
| Diffuser material:                | PC                      | HACCP:                       | <a href="#">852/2004</a>  |
| Diffuser type:                    | matrix led              | Manual:                      | <a href="#">Download PDF</a>  |
| Material of the body:             | galvanized coated steel | Plik LDT:                    | <a href="#">Download</a>  |

## LIGHT CURVES

