

LINEA S TRACK LED 590MM 2800LM 840 II CL. VW (17W) BLACK

DETAILED CARD



TECHNICAL PARAMETERS

Index:	765339
Ingress protection:	IP20
Impact resistance:	IK03
Rated power of the luminaire [W]*:	17
Luminous flux [lm]*:	2800
Colour temperature [K]:	4000
SDCM:	≤ 3
Energy efficiency class:	B
Material of the body:	powder coated steel
Colour of the body:	black

CHARACTERISTICS

Linea S Track LED is a linear alternative and complement to projectors with a COB LED light source. The modules are available in lengths of 590 and 1175 mm, with a variety of optics to suit particular concepts. Installation in a trunking system increases the range of applications and allows the user to make changes to the layout after installation. They are innovative, highly energy-efficient modules with excellent luminous efficiency and a minimalist, delicate appearance.

APPLICATION

The main areas of application are in the field of accent lighting in commercial buildings, museums, exhibition halls, offices, flats as an alternative or complement to rail-mounted projectors.


LINEA S TRACK LED 590MM 2800LM 840 II CL. VW (17W) BLACK

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Rated power of the luminaire [W]:	17	Surge protection [kV]:	2
Index:	765339	Colour of the body:	black
Colour temperature [K]:	4000	Diffuser material:	PC
EAN:	5905963765339	Dimensions (H/W/T/S) [mm]:	590/54/66
Luminous flux [lm]:	2800	Diffuser type:	matrix led
Light source:	LED	Material of the body:	powder coated steel
Energy efficiency class:	B	Impact resistance:	IK03
Supply voltage [V]:	220-240	Ingress protection:	IP20
Frequency [Hz]:	50-60	Mounting version:	track
Luminous efficacy [lm/W]:	165	Working temperature [°C]:	from -20 to +35
Electrical protection class:	II	Number on the palette [pcs]:	320
Colour rendering index:	>80	Net weight [kg]:	0.720
SDCM:	≤ 3	Category type:	systems
LED lifespan L70B50 [h]:	150000	AC voltage range [V]:	176-264
Beam angle [°]:	105	DC voltage range [V]:	176-280
LED lifespan L80B20 [h]:	100000	Warranty [years]:	5
Light distribution type:	VW	CE certificate:	74/2024
LED lifespan L90B10 [h]:	45000	Manual:	Download PDF
		Remarks:	RAL9005

LIGHT CURVES



Card creation date: 06 September 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 74/2024



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl