

LINEA S TRACK LED 1175MM 9050LM 840 II CL. 105D (61W) BLACK

DETAILED CARD



TECHNICAL PARAMETERS

| | |
|------------------------------------|---------------------|
| Index: | 765575 |
| Ingress protection: | IP20 |
| Impact resistance: | IK03 |
| Rated power of the luminaire [W]*: | 61 |
| Luminous flux [lm]*: | 9050 |
| Colour temperature [K]: | 4000 |
| SDCM: | 3 |
| Energy efficiency class: | C |
| Material of the body: | powder coated steel |
| Colour of the body: | black |

CHARACTERISTICS

Linea S Track LED is a linear alternative and complement to projectors with a COB LED light source. The modules are available in lengths of 590 and 1175 mm, with a variety of optics to suit particular concepts. Installation in a trunking system increases the range of applications and allows the user to make changes to the layout after installation. They are innovative, highly energy-efficient modules with excellent luminous efficiency and a minimalist, delicate appearance.

APPLICATION

The main areas of application are in the field of accent lighting in commercial buildings, museums, exhibition halls, offices, flats as an alternative or complement to rail-mounted projectors.

LINEA S TRACK LED 1175MM 9050LM 840 II CL. 105D (61W) BLACK

DETAILED CARD

TECHNICAL PARAMETERS TABLE

| | | | |
|-----------------------------------|---------------|--|--|
| Index: | 765575 | Diffuser type: | matrix led |
| EAN: | 5905963765575 | Material of the body: | powder coated steel |
| Light source: | LED | Colour of the body: | black |
| Rated power of the luminaire [W]: | 61 | Dimensions (H/W/T/S) [mm]: | 1175/54/66 |
| Supply voltage [V]: | 220-240 | Impact resistance: | IK03 |
| Frequency [Hz]: | 50-60 | Ingress protection: | IP20 |
| Luminous flux [lm]: | 9050 | Mounting version: | track |
| Luminous efficacy [lm/W]: | 148 | Working temperature [°C]: | from -20 to +35 |
| Energy efficiency class: | C | Number on the palette [pcs]: | 150 |
| Electrical protection class: | II | Net weight [kg]: | 1.200 |
| Colour temperature [K]: | 4000 | Category type: | luminaires and linear systems |
| Color rendering index (Ra) >: | 80 | AC voltage range [V]: | 176-264 |
| SDCM: | 3 | DC voltage range [V]: | 176-280 |
| LED lifespan L70B50 [h]: | 150000 | Warranty [years]: | 5 |
| LED lifespan L80B20 [h]: | 100000 | CE certificate: | 74/2024 |
| LED lifespan L90B10 [h]: | 45000 | Manual: | Download PDF |
| Beam angle [°]: | 105 | Environmental Product Declaration (EPD): | 852/2025 |
| Light distribution type: | symmetric | Remarks: | RAL9005 |
| Surge protection [kV]: | 2 | Category of application: | architectural, HoReCa, industrial, commercial facilities |
| Diffuser material: | PC | Plik LDT: | Download |

LIGHT CURVES

