LINEA S TRACK LED 1175MM 7900LM 840 II CL. SN (48W) BLACK

DETAILED CARD





TECHNICAL PARAMETERS

Index:	765667
Ingress protection:	IP20
Impact resistance:	IK03
Rated power of the luminaire [W]*:	48
Luminous flux [lm]*:	7900
Colour temperature [K]:	4000
SDCM:	≤3
Energy efficiency class:	В
Material of the body:	powder coated steel
Colour of the body:	black

CHARACTERISTICS

Linea S Track LED is a linear alternative and complement to projectors with a COB LED light source. The modules are available in lengths of 590 and 1175 mm, with a variety of optics to suit particular concepts. Installation in a trunking system increases the range of applications and allows the user to make changes to the layout after installation. They are innovative, highly energy-efficient modules with excellent luminous efficiency and a minimalist, delicate appearance.

APPLICATION

The main areas of application are in the field of accent lighting in commercial buildings, museums, exhibition halls, offices, flats as an alternative or complement to rail-mounted projectors.



LINEA S TRACK LED 1175MM 7900LM 840 II CL. SN (48W) BLACK


DETAILED CARD

TECHNICAL PARAMETERS TABLE

D	1.00
Rated power of the luminaire [W]:	48
Index:	765667
Colour temperature [K]:	4000
EAN:	5905963765667
Luminous flux [lm]:	7900
Light source:	LED
Energy efficiency class:	В
Supply voltage [V]:	220-240
Frequency [Hz]:	50-60
Luminous efficacy [lm/W]:	165
Electrical protection class:	II
Colour rendering index:	>80
SDCM:	≤ 3
LED lifespan L70B50 [h]:	150000
Beam angle [°]:	65
LED lifespan L80B20 [h]:	100000
Light distribution type:	SN
LED lifespan L90B10 [h]:	45000
Surge protection [kV]:	2

Colour of the body:	black
Diffuser material:	PC
Dimensions (H/W/T/S) [mm]:	1175/54/66
Diffuser type:	matrix led
Material of the body:	powder coated steel
Impact resistance:	IK03
Ingress protection:	IP20
Mounting version:	track
Working temperature [°C]:	from -20 to +35
Number on the palette [pcs]:	150
Net weight [kg]:	1.200
Category type:	systems
AC voltage range [V]:	176-264
DC voltage range [V]:	176-280
Warranty [years]:	5
CE certificate:	<u>74/2024</u>
Manual:	Download PDF
Remarks:	RAL9005
Category of application:	architectural, HoReCa, commercial facilities, industrial, art and culture
Plik LDT:	Download

LIGHT CURVES



Card creation date: 06 September 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



Page 2/2