


# LINEA S TRACK LED 1175MM 6400LM 840 II CL. VW (39W) WHITE

DETAILED CARD



## TECHNICAL PARAMETERS

|   |                     |
|---|---------------------|
| <b>Index:</b>                             | 766459              |
| <b>Ingress protection:</b>                | IP20                |
| <b>Impact resistance:</b>                 | IK03                |
| <b>Rated power of the luminaire [W]*:</b> | 39                  |
| <b>Luminous flux [lm]*:</b>               | 6400                |
| <b>Colour temperature [K]:</b>            | 4000                |
| <b>SDCM:</b>                              | ≤ 3                 |
| <b>Energy efficiency class:</b>           | B                   |
| <b>Material of the body:</b>              | powder coated steel |
| <b>Colour of the body:</b>                | white               |

## CHARACTERISTICS

Linea S Track LED is a linear alternative and complement to projectors with a COB LED light source. The modules are available in lengths of 590 and 1175 mm, with a variety of optics to suit particular concepts. Installation in a trunking system increases the range of applications and allows the user to make changes to the layout after installation. They are innovative, highly energy-efficient modules with excellent luminous efficiency and a minimalist, delicate appearance.

## APPLICATION

The main areas of application are in the field of accent lighting in commercial buildings, museums, exhibition halls, offices, flats as an alternative or complement to rail-mounted projectors.

# LINEA S TRACK LED 1175MM 6400LM 840 II CL. VW (39W) WHITE

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

|                                   |               |                              |                              |
|-----------------------------------|---------------|------------------------------|------------------------------|
| Index:                            | 766459        | Diffuser material:           | PC                           |
| EAN:                              | 5905963766459 | Diffuser type:               | matrix led                   |
| Light source:                     | LED           | Material of the body:        | powder coated steel          |
| Rated power of the luminaire [W]: | 39            | Colour of the body:          | white                        |
| Supply voltage [V]:               | 220-240       | Dimensions (H/W/T/S) [mm]:   | 1175/54/66                   |
| Frequency [Hz]:                   | 50-60         | Impact resistance:           | IK03                         |
| Luminous flux [lm]:               | 6400          | Ingress protection:          | IP20                         |
| Luminous efficacy [lm/W]:         | 164           | Mounting version:            | track                        |
| Energy efficiency class:          | B             | Working temperature [°C]:    | from -20 to +35              |
| Electrical protection class:      | II            | Number on the palette [pcs]: | 150                          |
| Colour temperature [K]:           | 4000          | Net weight [kg]:             | 1.200                        |
| Colour rendering index:           | >80           | Category type:               | systems                      |
| SDCM:                             | ≤ 3           | AC voltage range [V]:        | 176-264                      |
| LED lifespan L70B50 [h]:          | 150000        | DC voltage range [V]:        | 176-280                      |
| LED lifespan L80B20 [h]:          | 100000        | Warranty [years]:            | 5                            |
| LED lifespan L90B10 [h]:          | 45000         | CE certificate:              | <a href="#">74/2024</a>      |
| Beam angle [°]:                   | 105           | Manual:                      | <a href="#">Download PDF</a> |
| Light distribution type:          | VW            | Remarks:                     | RAL9016                      |
| Surge protection [kV]:            | 2             |                              |                              |

## LIGHT CURVES



Card creation date: 06 September 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 74/2024



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: [hello@lenalighting.pl](mailto:hello@lenalighting.pl), [www.lenalighting.pl](http://www.lenalighting.pl)