

# LINEA S TRACK LED 1175MM 7900LM 840 II CL. SN (48W) WHITE

DETAILED CARD



## TECHNICAL PARAMETERS

Index:	766824
Ingress protection:	IP20
Impact resistance:	IK03
Rated power of the luminaire [W]*:	48
Luminous flux [lm]*:	7900
Colour temperature [K]:	4000
SDCM:	≤ 3
Energy efficiency class:	B
Material of the body:	powder coated steel
Colour of the body:	white

## CHARACTERISTICS

Linea S Track LED is a linear alternative and complement to projectors with a COB LED light source. The modules are available in lengths of 590 and 1175 mm, with a variety of optics to suit particular concepts. Installation in a trunking system increases the range of applications and allows the user to make changes to the layout after installation. They are innovative, highly energy-efficient modules with excellent luminous efficiency and a minimalist, delicate appearance.

## APPLICATION

The main areas of application are in the field of accent lighting in commercial buildings, museums, exhibition halls, offices, flats as an alternative or complement to rail-mounted projectors.


# LINEA S TRACK LED 1175MM 7900LM 840 II CL. SN (48W) WHITE

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Index:	766824	Diffuser type:	matrix led
EAN:	5905963766824	Material of the body:	powder coated steel
Light source:	LED	Colour of the body:	white
Rated power of the luminaire [W]:	48	Dimensions (H/W/T/S) [mm]:	1175/54/66
Supply voltage [V]:	220-240	Impact resistance:	IK03
Frequency [Hz]:	50-60	Ingress protection:	IP20
Luminous flux [lm]:	7900	Mounting version:	track
Luminous efficacy [lm/W]:	165	Working temperature [°C]:	from -20 to +35
Energy efficiency class:	B	Number on the palette [pcs]:	150
Electrical protection class:	II	Net weight [kg]:	1.200
Colour temperature [K]:	4000	Category type:	luminaires and linear systems
Colour rendering index:	80	AC voltage range [V]:	176-264
SDCM:	≤ 3	DC voltage range [V]:	176-280
LED lifespan L70B50 [h]:	150000	Warranty [years]:	5
LED lifespan L80B20 [h]:	100000	CE certificate:	<a href="#">74/2024</a>
LED lifespan L90B10 [h]:	45000	Manual:	<a href="#">Download PDF</a>
Beam angle [°]:	65	Remarks:	RAL9016
Light distribution type:	SN	Category of application:	architectural, HoReCa, industrial, commercial facilities
Surge protection [kV]:	2	Plik LDT:	<a href="#">Download</a>
Diffuser material:	PC		

## LIGHT CURVES



Card creation date: 06 September 2024  
The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

This product is a subject to electric and electronic waste equipment regulations (WEEE).

Certificate CE - Nr: 74/2024



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: [hello@lenalighting.pl](mailto:hello@lenalighting.pl), [www.lenalighting.pl](http://www.lenalighting.pl)