

LINEA S TRACK LED 590MM 3750LM 840 II CL. SN (23W) WHITE

DETAILED CARD



TECHNICAL PARAMETERS

Index:	766893
Ingress protection:	IP20
Impact resistance:	IK03
Rated power of the luminaire [W]*:	23
Luminous flux [lm]*:	3750
Colour temperature [K]:	4000
SDCM:	3
Energy efficiency class:	B
Material of the body:	powder coated steel
Colour of the body:	white

CHARACTERISTICS

Linea S Track LED is a linear alternative and complement to projectors with a COB LED light source. The modules are available in lengths of 590 and 1175 mm, with a variety of optics to suit particular concepts. Installation in a trunking system increases the range of applications and allows the user to make changes to the layout after installation. They are innovative, highly energy-efficient modules with excellent luminous efficiency and a minimalist, delicate appearance.

APPLICATION

The main areas of application are in the field of accent lighting in commercial buildings, museums, exhibition halls, offices, flats as an alternative or complement to rail-mounted projectors.


LINEA S TRACK LED 590MM 3750LM 840 II CL. SN (23W) WHITE

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	766893	Material of the body:	powder coated steel
EAN:	5905963766893	Colour of the body:	white
Light source:	LED	Dimensions (H/W/T/S) [mm]:	590/54/66
Rated power of the luminaire [W]:	23	Impact resistance:	IK03
Supply voltage [V]:	220-240	Ingress protection:	IP20
Frequency [Hz]:	50-60	Mounting version:	track
Luminous flux [lm]:	3750	Working temperature [°C]:	from -20 to +35
Luminous efficacy [lm/W]:	163	Number on the palette [pcs]:	320
Energy efficiency class:	B	Net weight [kg]:	0.720
Electrical protection class:	II	Category type:	luminaires and linear systems
Colour temperature [K]:	4000	AC voltage range [V]:	176-264
Color rendering index (Ra) >:	80	DC voltage range [V]:	176-280
SDCM:	3	Warranty [years]:	5
LED lifespan L70B50 [h]:	150000	CE certificate:	74/2024
LED lifespan L80B20 [h]:	100000	Manual:	Download PDF
LED lifespan L90B10 [h]:	45000	Environmental Product Declaration (EPD):	852/2025
Beam angle [°]:	65	Remarks:	RAL9016
Light distribution type:	SN	Category of application:	architectural, HoReCa, industrial, commercial facilities
Surge protection [kV]:	2	Mark D:	yes
Diffuser material:	PC	ISO Certificates:	9001:2015, 14001:2015, 45001:2018, 50001:2018
Diffuser type:	matrix led	Plik LDT:	Download

LIGHT CURVES



Card creation date: 16 December 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 74/2024