

STRADO LED XS 5525LM 740 RM7 IP66 II CL. 2DIM (39W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	870712
Ingress protection:	IP66
Impact resistance:	IK10
Rated power of the luminaire [W]*:	39
Luminous flux [lm]*:	5525
Colour temperature [K]:	4000
Colour rendering index:	> 70
Electrical protection class:	II
Optics:	RM7
Control:	Yes + 5-stage power reduction

CHARACTERISTICS

Strado LED XS is a new family of LED road luminaires. It uses directional multi-lens matrices, made of PMMA, with each lens having the same optics, ensuring that the luminous characteristics remain constant over time. Components from renowned manufacturers and state-of-the-art LED panels contribute to the very high luminous efficacy achieved at the output of the luminaire - reaching 155 lm/W. The upper part of the body has a separate electrical cavity in the body, which allows for efficient cooling of all power supply components, independently of the light module. The lower surface of the luminaire is finished entirely with toughened glass, providing high aesthetic qualities. The luminaire has an outgoing cable with a quick-release connector, which allows fast, convenient and reliable installation without opening the luminaire. Using standard tools, it is possible to service the luminaire, allowing any component to be replaced without soldering. The body and fixture are made of die-cast aluminium, powder-coated grey, and have a very high IP66 ingress protection rating and IK09; IK10 mechanical impact resistance. Standard features: fully programmable DALI driver; available functions for maintaining constant luminous flux during CLO and autonomous 5-step power reduction; NTC protection against accidental overheating of the luminaire; filter to prevent condensation; outgoing cable with quick-connector. Additional options: NEMA, ZHAGA connectors on the top of the luminaire; interfacing with control systems; additional SP10kV protection outside the power supply, on/off power supply without power reduction function; painting in any RAL colour. Certifications: CE, Zhaga D4i, ENEC, ENEC+.

APPLICATION

Thanks to the use of dedicated optics, it is possible to illuminate objects such as: highways, expressways, national, provincial, county, municipal, city, neighborhood, area lighting. Optics are also available to illuminate: pedestrian crossings, sidewalks and bicycle paths.


STRADO LED XS 5525LM 740 RM7 IP66 II CL. 2DIM (39W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	870712	Optics material:	PMMA
Rated power of the luminaire [W]:	39	Optics:	RM7
EAN:	5905963870712	Exchangeable source:	yes
Luminous flux [lm]:	5525	Material of the body:	aluminium
Category type:	street lighting	Colour of the body:	grey
Luminous efficacy [lm/W]:	142	Dimensions (H/W/T/S) [mm]:	449/185/85
Version:	XS	Mounting dimensions [mm]:	ø60
Colour temperature [K]:	4000	Ingress protection:	IP66
Light source:	LED module	Mounting version:	Top, on pole / Side, on boom
Colour rendering index:	> 70	Tilt angle adjustment [°]:	`od -20° do 20°
Supply voltage [V]:	220 – 240	Lateral surface (SCx) [m2]:	0.018
Frequency [Hz]:	50 - 60	Working temperature [°C]:	from -40 to +50
Impact resistance:	IK10	DIMM 1-10V:	yes
Vandalproof:	yes	Net weight [kg]:	3.900
Energy efficiency class:	C	ULOR:	0%
Control:	Yes + 5-stage power reduction	Photobiological safety:	RG0 - exempt (no photobiological hazard)
Electrical protection class:	II	Technical Warranty:	5 with the possibility of extension to 10
Protection type:	NTC + ESD	ENEC Certificate:	0390/ENEC/24; 0133/ENEC+/24
SDCM:	≤ 4	CE certificate:	76/2024
Power factor:	0.95	Zhaga-D4i:	ZG436418112024
Diffuser material:	toughened glass	Environmental Product Declaration (EPD):	682/2024
Diffuser type:	transparent	Manual:	Download PDF
		LED lifespan L95B10 [h]:	100000

LIGHT CURVES



STRADO LED XS 5525LM 740 RM7 IP66 II CL. 2DIM (39W)

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
314049	wall holder (galvanized)
314056	wall holder (grey)



wall holder (galvanized) (314049)



wall holder (grey) (314056)

Card creation date: 29 November 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 76/2024