

# TAURUS MULTIBATTERY LED

DETAILED CARD



## TECHNICAL PARAMETERS

Index:	256882
Ingress protection:	IP65
Impact resistance:	IK08
Colour temperature [K] - range:	2700 - 6500
Luminous flux [lm]*:	5000
Supply voltage [V]:	18
Electrical protection class:	III
Material of the body:	PP
Colour of the body:	green
Diffuser type:	milky

## CHARACTERISTICS

Compact LED floodlight for professional use. Provides even and stable directional illumination. Made from impact-resistant polypropylene (PP). Smaller size and compact design make it more convenient to transport. Equipped with an on/off switch with 4-stage luminous flux adjustment. An additional button allows adjustment of the light colour in the range: 2700K to 6500K. The lamp is compatible with 18V batteries from manufacturers such as Bosch (18V Professional), Milwaukee, DeWalt, Metabo. The unit has a display showing the battery charge level.

Operating modes for battery operation:

- for 5Ah Battery:
- 500 lm - operating time: 20h
  - 1850 lm - operating time: 7h 15min
  - 2750 lm - operating time: 4h 30min
  - 4050 lm - operating time: 2h 15min

## APPLICATION

It can be used as a workplace luminaire to illuminate workplaces, workshops or garages.

# TAURUS MULTIBATTERY LED

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Index:	256882	Impact resistance:	IK08
Light source:	LED module	Ingress protection:	IP65
Colour temperature [K] - range:	2700 - 6500	Net weight [kg]:	2.770
Luminous flux [lm]:	5000	Category type:	workplace floodlights
Supply voltage [V]:	18	LED lifespan L70B50 [h]:	140000
Electrical protection class:	III	LED lifespan L80B20 [h]:	85000
Colour rendering index:	>80	LED lifespan L90B10 [h]:	42000
Additional accessories:	Adapter for Bosch 18V. Milwaukee 18V, DeWalt 18V, Makita 18V and Metabo 18V batteries.	Light distribution type:	lamertian
SDCM:	≤ 3	ETIM class:	EC000346
Dimensions (H/W/T/S) [mm]:	280/280/148	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Beam angle [°]:	120	Warranty [years]:	2
Diffuser type:	milky	CE certificate:	<a href="#">77/2024</a>
Material of the body:	PP	Manual:	<a href="#">Download PDF</a>
Colour of the body:	green		

Card creation date:15 October 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

 This product is a subject to electric andelectronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 77/2024



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: [hello@lenalighting.pl](mailto:hello@lenalighting.pl), [www.lenalighting.pl](http://www.lenalighting.pl)