

TAURUS MULTIBATTERY LED

DETAILED CARD



TECHNICAL PARAMETERS

| | |
|--|-------------|
| Index: | 256882 |
| Ingress protection: | IP65 |
| Impact resistance: | IK08 |
| Colour temperature [K] - range: | 2700 - 6500 |
| Luminous flux [lm]*: | 5000 |
| Supply voltage [V]: | 18 |
| Electrical protection class: | III |
| Material of the body: | PP |
| Colour of the body: | green |
| Diffuser type: | milky |

CHARACTERISTICS

Compact LED floodlight for professional use. Provides even and stable directional illumination. Made from impact-resistant polypropylene (PP). Smaller size and compact design make it more convenient to transport. Equipped with an on/off switch with 4-stage luminous flux adjustment. An additional button allows adjustment of the light colour in the range: 2700K to 6500K. The lamp is compatible with 18V batteries from manufacturers such as Bosch (18V Professional), Milwaukee, DeWalt, Metabo. The unit has a display showing the battery charge level.

Operating modes for battery operation:

for 5Ah Battery:

- 500 lm - operating time: 20h
- 1500 lm - operating time: 7h 15min
- 2500 lm - operating time: 4h 30min
- 5000 lm - operating time: 2h 15min

APPLICATION

It can be used as a workplace luminaire to illuminate workplaces, workshops or garages.

TAURUS MULTIBATTERY LED

DETAILED CARD

TECHNICAL PARAMETERS TABLE

| | | | |
|---|-------------|---------------------------------|---|
| Index: | 256882 | Ingress protection: | IP65 |
| Light source: | LED module | Net weight [kg]: | 2.770 |
| Luminous flux [lm]: | 5000 | Category type: | workplace floodlights |
| Colour temperature [K] - range: | 2700 - 6500 | LED lifespan L70B50 [h]: | 140000 |
| Supply voltage [V]: | 18 | LED lifespan L80B10 [h]: | 85000 |
| Electrical protection class: | III | LED lifespan L90B10 [h]: | 42000 |
| Color rendering index (Ra) >: | 80 | Light distribution type: | lambertian |
| SDCM: | 3 | Additional accessories: | Adapter for Bosch 18V, Milwaukee 18V, DeWalt 18V, Makita 18V and Metabo 18V batteries. |
| Beam angle [°]: | 120 | ETIM class: | EC000346 |
| Diffuser type: | milky | Photobiological safety: | Risk Group 1 (no photobiological hazard under normal behavioral limitation) |
| Material of the body: | PP | Warranty [years]: | 2 |
| Colour of the body: | green | CE certificate: | 77/2024 |
| Dimensions (H/W/T/S) [mm]: | 280/280/148 | Manual: | Download PDF |
| Impact resistance: | IK08 | | |

Card creation date: 30 July 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 77/2024



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl