

# TAURUS MULTIBATTERY LED

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Index:</b>	256882
<b>Ingress protection:</b>	IP65
<b>Impact resistance:</b>	IK08
<b>Colour temperature [K] - range:</b>	2700 - 6500
<b>Luminous flux [lm]*:</b>	5000
<b>Supply voltage [V]:</b>	18
<b>Electrical protection class:</b>	III
<b>Material of the body:</b>	PP
<b>Colour of the body:</b>	green
<b>Diffuser type:</b>	milky

## CHARACTERISTICS

Compact LED floodlight for professional use. Provides even and stable directional illumination. Made from impact-resistant polypropylene (PP). Smaller size and compact design make it more convenient to transport. Equipped with an on/off switch with 4-stage luminous flux adjustment. An additional button allows adjustment of the light colour in the range: 2700K to 6500K. The lamp is compatible with 18V batteries from manufacturers such as Bosch (18V Professional), Milwaukee, DeWalt, Metabo. The unit has a display showing the battery charge level.

Operating modes for battery operation:

for 5Ah Battery:

- 500 lm - operating time: 20h
- 1850 lm - operating time: 7h 15min
- 2750 lm - operating time: 4h 30min
- 4050 lm - operating time: 2h 15min

## APPLICATION

It can be used as a workplace luminaire to illuminate workplaces, workshops or garages.

# TAURUS MULTIBATTERY LED

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

<b>Index:</b>	256882	<b>Ingress protection:</b>	IP65
<b>Light source:</b>	LED module	<b>Net weight [kg]:</b>	2.770
<b>Luminous flux [lm]:</b>	5000	<b>Category type:</b>	workplace floodlights
<b>Colour temperature [K] - range:</b>	2700 - 6500	<b>LED lifespan L70B50 [h]:</b>	140000
<b>Supply voltage [V]:</b>	18	<b>LED lifespan L80B20 [h]:</b>	85000
<b>Electrical protection class:</b>	III	<b>LED lifespan L90B10 [h]:</b>	42000
<b>Colour rendering index:</b>	>80	<b>Light distribution type:</b>	lambertian
<b>SDCM:</b>	≤ 3	<b>Additional accessories:</b>	Adapter for Bosch 18V, Milwaukee 18V, DeWalt 18V, Makita 18V and Metabo 18V batteries.
<b>Beam angle [°]:</b>	120	<b>ETIM class:</b>	EC000346
<b>Diffuser type:</b>	milky	<b>Photobiological safety:</b>	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
<b>Material of the body:</b>	PP	<b>Warranty [years]:</b>	2
<b>Colour of the body:</b>	green	<b>CE certificate:</b>	<a href="#">77/2024</a>
<b>Dimensions (H/W/T/S) [mm]:</b>	280/280/148	<b>Manual:</b>	<a href="#">Download PDF</a>
<b>Impact resistance:</b>	IK08		

Card creation date: 15 October 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 77/2024



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl