

# ILUMI BOLLARD 600 1100LM 830 IP65 I CL. 360° ANTRACITE 24W

DETAILED CARD



## TECHNICAL PARAMETERS

Index:	377303
Rated power of the luminaire [W]*:	24
Ingress protection:	IP65
Impact resistance:	IK10
Luminous flux [lm]*:	1100
Colour temperature [K]:	3000
Material of the body:	aluminium
Colour of the body:	antracyt
Beam angle [°]:	360
Dimensions (H/W/T/S) [mm]:	600/fi170

## CHARACTERISTICS

The Bollard series has been designed using modern simulation methods to achieve the highest product quality. A product based on LEDs from the renowned American company CREE® IP67. The luminaire is made of aluminium. Power supply 220-240V AC. 5-year warranty. Power: 24W.

## APPLICATION

Bollard outdoor luminaires can be used to light and illuminate a wide range of locations and objects, including but not limited to:

- \* parks,
- \* gardens,
- \* monuments,
- \* squares,
- \* fountains.

# ILUMI BOLLARD 600 1100LM 830 IP65 I CL. 360° ANTRACITE 24W

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Index:	377303	Ring material:	aluminium
EAN:	5905963377303	Ring colour:	black
Light source:	LED module	Dimensions (H/W/T/S) [mm]:	600/φ170
Rated power of the luminaire [W]:	24	Impact resistance:	IK10
Supply voltage [V]:	220 - 240	Ingress protection:	IP65
Frequency [Hz]:	50 - 60	Working temperature [°C]:	from -20 to +55
Luminous flux [lm]:	1100	Control:	ON/OFF
Electrical protection class:	I	Cable length [m]:	0.50
Colour temperature [K]:	3000	LED lifespan L90B10 [h]:	65000
Colour rendering index:	80	Category type:	accent lighting
Beam angle [°]:	360	CE certificate:	<a href="#">78/2024</a>
Material of the body:	aluminium	Warranty [years]:	5
Colour of the body:	antracyt	Manual:	<a href="#">Download PDF</a>

## LIGHT CURVES

