

ILUMI BOLLARD 1000 1100LM 830 IP65 I CL. 360° ANTRACITE 24W

DETAILED CARD



TECHNICAL PARAMETERS

Index:	377310
Rated power of the luminaire [W]*:	24
Ingress protection:	IP65
Impact resistance:	IK10
Luminous flux [lm]*:	1100
Colour temperature [K]:	3000
Material of the body:	aluminium
Colour of the body:	antracyt
Beam angle [°]:	360
Dimensions (H/W/T/S) [mm]:	1000/fi170

CHARACTERISTICS

The Bollard series has been designed using modern simulation methods to achieve the highest product quality. A product based on LEDs from the renowned American company CREE® IP67. The luminaire is made of aluminium. Power supply 220-240V AC. 5-year warranty. Power: 24W.

APPLICATION

Bollard outdoor luminaires can be used to light and illuminate a wide range of locations and objects, including but not limited to:

- * parks,
- * gardens,
- * monuments,
- * squares,
- * fountains.

ILUMI BOLLARD 1000 1100LM 830 IP65 I CL. 360°

ANTRACITE 24W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	377310	Ring material:	aluminium
EAN:	5905963377310	Ring colour:	black
Light source:	LED module	Dimensions (H/W/T/S) [mm]:	1000/fi170
Rated power of the luminaire [W]:	24	Impact resistance:	IK10
Supply voltage [V]:	220 - 240	Ingress protection:	IP65
Frequency [Hz]:	50 - 60	Working temperature [°C]:	from -20 to +55
Luminous flux [lm]:	1100	Control:	ON/OFF
Electrical protection class:	I	Cable length [m]:	0.50
Colour temperature [K]:	3000	LED lifespan L90B10 [h]:	65000
Colour rendering index:	80	Category type:	accent lighting
Beam angle [°]:	360	CE certificate:	78/2024
Material of the body:	aluminium	Warranty [years]:	5
Colour of the body:	antracyt	Manual:	Download PDF

LIGHT CURVES

