ILUMI BOLLARD 1000 1100LM 830 IP65 I CL. 360° ANTRACITE 24W

DETAILED CARD





TECHNICAL PARAMETERS

Index:	377310
Rated power of the luminaire [W]*:	24
Ingress protection:	IP65
Impact resistance:	IK10
Luminous flux [lm]*:	1100
Colour temperature [K]:	3000
Material of the body:	aluminium
Colour of the body:	antracyt
Beam angle [°]:	360
Dimensions (H/W/T/S) [mm]:	1000/fi170

CHARACTERISTICS

The Bollard series has been designed using modern simulation methods to achieve the highest product quality. A product based on LEDs from the renowned American company CREE® IP67. The luminaire is made of aluminium. Power supply 220-240V AC. 5-year warranty. Power: 24W.

APPLICATION

Bollard outdoor luminaires can be used to light and illuminate a wide range of locations and objects, including but not limited to:

- * parks,
- * gardens,
- * monuments,
- * squares,
- * fountains.



ILUMI BOLLARD 1000 1100LM 830 IP65 I CL. 360° ANTRACITE 24W


DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	377310
EAN:	5905963377310
Light source:	LED module
Rated power of the luminaire [W]:	24
Supply voltage [V]:	220 - 240
Frequency [Hz]:	50 - 60
Luminous flux [lm]:	1100
Electrical protection class:	I
Colour temperature [K]:	3000
Colour rendering index:	80
Beam angle [°]:	360
Material of the body:	aluminium
Colour of the body:	antracyt

Ring material:	aluminium
Ring colour:	black
Dimensions (H/W/T/S) [mm]:	1000/fi170
Impact resistance:	IK10
Ingress protection:	IP65
Working temperature [°C]:	from -20 to +55
Control:	ON/OFF
Cable length [m]:	0.50
LED lifespan L90B10 [h]:	65000
Category type:	accent lighting
CE certificate:	78/2024
Warranty [years]:	5
Manual:	Download PDF

LIGHT CURVES



Card creation date: 17 October 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



